Package 'GGIRread'

March 28, 2024

```
Type Package
Title Wearable Accelerometer Data File Readers
Version 1.0.0
Date 2024-03-27
Maintainer Vincent T van Hees <v.vanhees@accelting.com>
Description Reads data collected from wearable acceleratometers as used in sleep and physical activ-
      ity research. Currently supports file formats: binary data from 'GENEAc-
      tiv' < https://activinsights.com/>, .bin-format from GENEA de-
      vices (not for sale), and .cwa-format from 'Axivity' <a href="https://axivity.com">https://axivity.com</a>. Primarily de-
      signed to complement R package GGIR <a href="https://CRAN.R-project.org/package=GGIR">https://CRAN.R-project.org/package=GGIR</a>>.
URL https://github.com/wadpac/GGIRread/
BugReports https://github.com/wadpac/GGIRread/issues
License Apache License (== 2.0)
Suggests testthat
Imports matlab, bitops, Rcpp (>= 0.12.10)
Depends stats, utils, R (>= 3.5.0)
NeedsCompilation yes
LinkingTo Rcpp
ByteCompile yes
Author Vincent T van Hees [aut, cre],
      Patrick Bos [aut] (<a href="https://orcid.org/0000-0002-6033-960X">https://orcid.org/0000-0002-6033-960X</a>),
      Lena Kushleyeva [ctb],
      Jing Hua Zhao [ctb],
      Evgeny Mirkes [ctb],
      Dan Jackson [ctb],
      Jairo H Migueles [ctb],
      Medical Research Council UK [cph, fnd],
      Accelting [cph, fnd]
Repository CRAN
Date/Publication 2024-03-28 08:10:10 UTC
```

2 GGIRread-package

R topics documented:

| GGIR | read-package | A | pι | acl | ka, | ge | to |) r | ·ес | ıd | da | ita | ı fi | ile | s f | ro | m | w | ea | ıra | bl | e a | ıc | cei | eı | or | ne | te | rs | | | | |
|-------|------------------|---|----|-----|-----|----|----|-----|-----|----|----|-----|------|-----|-----|----|---|---|----|-----|----|-----|----|-----|----|----|----|----|----|---|---|---|-----|
| Index | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | 10 |
| | resample | • | | | • | • | • | • | • | • | | | • | • | • | | | • | | | • | • | • | • | • | | • | • | • | • | • | • | . 9 |
| | readWav | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | readGENEActiv | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | readGenea | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | . (|
| | readAxivity | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | . 4 |
| | GENEActivReader | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | . 3 |
| | GGIRread-package | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | . 2 |

Description

This package offers a collection of functions to read data files from wearable accelerometers. Some functions were migrated from R package GGIR to make GGIR more modular and to reduce it's complexity, while other functions such as readGENEActiv (R) and GENEActivReader (C++) are newly written.

Details

Package: GGIRread
Type: Package
Version: 1.0.0
Date: 2024-03-27
License: LGPL (>= 2.0, < 3)

Author(s)

- Vincent T van Hees <v.vanhees@accelting.com> main creator and developer
- Patrick Bos developed function GENEActivReader
- Jing Hua Zhao <jinghua.zhao@mrc-epid.cam.ac.uk> co-developed function readGenea
- Evgeny Mirkes created function readAxivity
- Dan Jackson helped improve function readAxivity

GENEActivReader 3

| GENEActivReader | Function (C++) to read binary files as produced by the GENEActiv accelerometer |
|-----------------|--|
| | |

Description

Function to read binary files as produced by the GENEActiv accelerometer by ActivInsights Ltd https://activinsights.com/

Usage

```
GENEActivReader(filename, start = 0L, end = 0L, progress_bar = FALSE)
```

Arguments

| filename | filename (required) |
|--------------|-----------------------------|
| start | start page for reading data |
| end | end page for reading data |
| progress_bar | Boolean |

Details

If only start page is defined then all data is read beyond start until the end of the file is reached

Value

| info | List with ReadOK (good=0 or error=1), ReadErrors (Count of pages with read errors), SampleRate (Hertz), numBlocksTotal |
|-------------|--|
| time | Numeric vector with time in miliseconds since start page |
| x | Numeric vector with x-axis acceleration in gravitational units |
| У | Numeric vector with y-axis acceleration in gravitational units |
| Z | Numeric vector with z-axis acceleration in gravitational units |
| temperature | matrix with battery voltage and corresponding timestamps |
| lux | Numeric vector with lux values in Volts |

Author(s)

Patrick Bos <egpbos@gmail.com> Vincent T van Hees <v.vanhees@accelting.com>

4 readAxivity

| readAxivity | Function to read .cwa-format files as produced by the accelerometer named 'Axivity' |
|-------------|---|
| | |

Description

For reading .cwa-format data with the Axivity AX3 and AX6 sensors.

Usage

```
readAxivity(filename, start = 0, end = 0, progressBar = FALSE,
  desiredtz = "", configtz = c(), interpolationType=1, loadbattery = FALSE,
  header = NULL, frequency_tol = 0.1, maxAllowedCorruptBlocks = 20)
```

Arguments

| filename | filename (| (required) | is name of | cwa file to | read |
|----------|------------|------------|------------|-------------|------|
|----------|------------|------------|------------|-------------|------|

start non-negative integer which is a cwa file block number.

end non-negative integer which is a cwa file block number. End must be not be less

than start. If end is less or equal to start, then there is no data read.

progressBar Is trigger to switch on/off the text progress bar. If progressBar is TRUE then the

function displays the progress bar but it works slightly slower

desiredtz Desired timezone, a character with timezone database name.

configtz Only functional for AX3 cwa data at the moment. Timezone in which the ac-

celerometer was configured. Only use this argument if the timezone of configu-

ration and timezone in which recording took place are different.

interpolationType

Integer to indicate type of interpolation to be used, 1=linear, 2=nearest neigh-

bour.

loadbattery Boolean to indicate whether battery voltage should be loaded

header Header to be reused if it was extracted earlier

frequency_tol Numeric value representing the tolerance for frequency bias expressed as a frac-

tion of the expected sampling frequency. For example, 0.10 indicates that we accept the sampling frequency configured at 100 Hertz to vary between 90 and 110 Hertz. If this condition is not met the data will be imputed with a constant value and the start and end time will be logged in the QClog output object. Regardless of the setting the function will always log instances when frequency differs by more than 5%, but if this is less than frequency_tol the block will not

be imputed.

maxAllowedCorruptBlocks

Max number of consecutive blocks with a failed checksum that we'll tolerate.

readAxivity 5

Value

• data dataframe with data from start inclusive till end exclusive. If start == end then data section of final structure is empty.

- timestamp in numeric format
- gx gyroscope x-axis (only available in AX6)
- gy gyroscope y-axis (only available in AX6)
- gz gyroscope z-axis (only available in AX6)
- x accelerometer x-axis
- y accelerometer y-axis
- z accelerometer z-axis
- temperature in Celsius (only recorded once per block)
- battery one value per block (only recorded once per block)
- light in LUX on (only recorded once per block)
- header file header. list of header information:
 - uniqueSerialCode is unque serial code of used device
 - frequency is measurement frequency. All data will be resampled for this frequency
 - start is timestamp in numeric form. To get text representation it is enough to use as.POSIXct(start, origin = "1970-01-01", tz=desiredtz)
 - device is "Axivity"
 - firmwareVersion
 - blocks is number of datablocks with 80 or 120 raw observations in each.
- QClog dataframe with log of integrity checks on each block including:
 - checksum_pass Boolean to indicate whether checksum was zero.
 - blockID_previous ID for previous block
 - blockID_current ID for current block
 - start_previous numeric start time of previous block
 - start current numeric start time of current block
 - blockLengthSeconds length of previous block
 - frequency_blockheader frequency derived from block header
 - frequency_observed frequency as observed
 - imputed Boolean to indicate whether this block was inputed

Author(s)

Evgeny Mirkes <em322@leicester.ac.uk> Lena Kushleyeva Vincent van Hees <v.vanhees@accelting.com>

Examples

```
cwafile = system.file("testfiles/ax3_testfile.cwa", package = "GGIRread")[1]
AX3 = readAxivity(filename = cwafile, desiredtz = "Europe/Berlin", start = 1, end = 2)
```

6 readGenea

| readGenea | Function to read binary files as produced by the accelerometer named |
|-----------|--|
| | 'Genea', not to be confused with the 'GENEActiv' (see package GEN-EAread for this) |

Description

For reading the binary data as collected with a Genea accelerometer (Unilever Discover, UK). For reading GENEActive binary data, see package GENEAread.

Usage

```
readGenea(filename, start = 0, end = 0)
```

Arguments

| filename | filename (required) |
|----------|--|
| start | start point for reading data, this can either be a timestamp in POSIXct format "year-month-day hr:min:sec" or a page number (optional) |
| end | end point for reading data, this can either be a timestamp in POSIXct format |

"year-month-day hr:min:sec" or a page number (optional)

Details

If only start is defined then readGenea will read all data beyond start until the end of the file is reached

Value

| rawxyz | matrix with raw x, y, and, z acceleration values |
|--------------|--|
| header | file header |
| timestamps1 | timestamps for rawxyz in seconds since 1970-01-01 00:00 |
| timestamps2 | timestamps for rawxyz in day time format |
| batt.voltage | matrix with battery voltage and corresponding timestamps |

Author(s)

Vincent T van Hees <v.vanhees@accelting.com> Jing Hua Zhao <jinghua.zhao@mrc-epid.cam.ac.uk>

Examples

```
geneafile = system.file("testfiles/genea_testfile.bin", package = "GGIRread")[1]
GENEA = readGenea(filename = geneafile, start = 0, end = 2)
```

readGENEActiv 7

| readGENEActiv | Function (R) to read binary files as produced by the GENEActiv accelerometer |
|---------------|--|
| | celerometer |

Description

R function wrapper around GENEActivReader to read binary files as produced by the GENEActiv accelerometer by ActivInsights Ltd https://activinsights.com/

Usage

Arguments

filename (required)
start start page for reading data
end end page for reading data

progress_bar Boolean

desiredtz Character, timezone database name of the timezone where the accelerometer

was worn.

configtz Character, timezone database name of the timezone where the accelerometer

was configured. Leave NULL if equal to timezone where experiment took place.

Details

If only start page is defined then all data is read beyond start until the end of the file is reached

Value

header:

serial_number Device serial number as extracted from file header

firmware Firmware version

tzone Time zone as extracted from file header

ReadOK see GENEActivReader

SampleRate matrix with battery voltage and corresponding timestamps matrix with battery voltage and corresponding timestamps numBlocksTotal matrix with battery voltage and corresponding timestamps

StartTime Start time as extracted from file header

data.out:

8 readWav

| time | Unix time in seconds with decimal places for miliseconds |
|-------------|--|
| X | see GENEActivReader |
| у | see GENEActivReader |
| z | see GENEActivReader |
| light | Ligth values express in lux units |
| temperature | Temperature in Celsius |

Author(s)

Patrick Bos <egpbos@gmail.com> Vincent T van Hees <v.vanhees@accelting.com>

Examples

```
binfile = system.file("testfiles/GENEActiv_testfile.bin", package = "GGIRread")[1]
rdata = readGENEActiv(filename = binfile, start = 1, end = 1, desiredtz = "Europe/London")
```

| readWav | Deprecated function to read .wav files as can be stored with OMGUI software by Axivity Ltd |
|---------|--|
| | |

Description

Originally designed to read the wav accelerometer data format as stored with the OMGUI software by Axivity Ltd and documented here.

This function has been deprecated as way files are hardly used, their formatting is not consistent causing ongoing challenges with keeping the keep functional, way format not well facilitated for AX6 recording.

Usage

```
readWav(filename, start = 1, end = 100,units="minutes")
```

Arguments

| filename | filename (required) |
|----------|--|
| start | start point for reading data, see also units |
| end | end point for reading data, see also units |
| units | units used for defining start and end |

Details

If only start is defined then g.binread will read all data beyond start until the end of the file is reached

resample 9

Value

rawxyz matrix with raw x, y, and, z acceleration values

header file header

timestamps local timestamps for rawxyz

Author(s)

Vincent T van Hees <v.vanhees@accelting.com>

resample Resample timeseries

Description

Resample single- or multi-variate time series using linear or nearest neighbour interpolation

Usage

```
resample(raw, rawTime, time, stop, type = 1)
```

Arguments

raw stop-by-3 matrix with raw values of x, y and z.

rawTime vector with stop elements of raw time.

time array with required time points.

stop Number of rows in raw

type integer to indicate type of interpolation, 1=linear, 2=nearest neighbour

Examples

```
raw = cbind(1:10, 1:10, 1:10)
rawTime = seq(0.1, 1, by = 0.1)
time = seq(0.15001, 1.05001, by = 0.1)
stop = 10
dat_lin = resample(raw, rawTime, time, stop, type = 1)
```

Index

```
GENEActivReader, 2, 3, 7, 8
GGIRread-package, 2
readAxivity, 2, 4
readGenea, 2, 6
readGENEActiv, 7
readWav, 8
resample, 9
```