

# Package ‘WikipediR’

January 20, 2025

**Type** Package

**Title** A MediaWiki API Wrapper

**Version** 1.7.1

**Date** 2024-04-05

**Author** Os Keyes [aut, cre], Brock Tilbert [ctb], Clemens Schmid [aut]

**Maintainer** Os Keyes <ironholds@gmail.com>

**Description** A wrapper for the MediaWiki API, aimed particularly at the Wikimedia 'production' wikis, such as Wikipedia. It can be used to retrieve page text, information about users or the history of pages, and elements of the category tree.

**License** MIT + file LICENSE

**Imports** httr, jsonlite, magrittr

**Suggests** testthat, knitr, WikidataR, pageviews

**BugReports** <https://github.com/Ironholds/WikipediR/issues>

**URL** <https://github.com/Ironholds/WikipediR/>

**VignetteBuilder** knitr

**RoxygenNote** 7.3.1

**Encoding** UTF-8

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2024-04-05 18:13:00 UTC

## Contents

categories_in_page . . . . .	2
create_page . . . . .	3
create_pages . . . . .	4
get_action_token . . . . .	5
get_prelogin_token . . . . .	5

login . . . . .	6
pages_in_category . . . . .	6
page_backlinks . . . . .	8
page_content . . . . .	9
page_external_links . . . . .	10
page_info . . . . .	11
page_links . . . . .	12
parse_response . . . . .	13
query . . . . .	14
random_page . . . . .	14
recent_changes . . . . .	15
revision_content . . . . .	17
revision_diff . . . . .	18
user_contributions . . . . .	20
user_information . . . . .	21
WikipediR . . . . .	23

## Index 24

---

categories_in_page	<i>Retrieves categories associated with a page.</i>
--------------------	---

---

### Description

Retrieves categories associated with a page (or list of pages) on a MediaWiki instance

### Usage

```
categories_in_page(
  language = NULL,
  project = NULL,
  domain = NULL,
  pages,
  properties = c("sortkey", "timestamp", "hidden"),
  limit = 50,
  show_hidden = FALSE,
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.

pages	A vector of page titles, with or without spaces, that you want to retrieve categories for.
properties	The properties you want to retrieve about the categories. Options are "sortkey" (the key that sorts the way the page is stored in each category), "timestamp" (when the category was added to that page) and "hidden" (tags those categories in the returned list that are 'hidden' from readers).
limit	The maximum number of categories you want to retrieve for each page. Set to 50 by default.
show_hidden	Whether or not to include 'hidden' categories in the categories that are retrieved - these are usually associated with the maintenance of Wikipedia and its internal processes. Set to FALSE by default.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

**See Also**

[pages\\_in\\_category](#) for pages in a specified category.

**Examples**

```
## Not run:
#Retrieve the categories for the "New Age" article on en.wiki
cats <- categories_in_page("en", "wikipedia", pages = "New Age")

#Retrieve the categories for the "New Age" article on rationalwiki.
rw_cats <- categories_in_page(domain = "rationalwiki.org", pages = "New Age")

## End(Not run)
```

---

create_page	<i>wikimedia api page creation (single pages) helper function to do the actual api requests for page and category-page creation</i>
-------------	---

---

**Description**

wikimedia api page creation (single pages)

helper function to do the actual api requests for page and category-page creation

**Usage**

```
create_page(url, p_title, p_text, category, token)
```

**Arguments**

url	a URL body
p_title	page title string of new page
p_text	page content string of new page
category	switch to decide, if the page should be created as category-page
token	action token to perform the request

**Value**

TRUE

---

create_pages	<i>wikimedia api page creation Create pages or category-pages on a wikimedia instance.</i>
--------------	--

---

**Description**

wikimedia api page creation

Create pages or category-pages on a wikimedia instance.

**Usage**

```
create_pages(url, p_title, p_text, category = FALSE)
```

**Arguments**

url	a URL body
p_title	vector with page title strings of new pages
p_text	vector with page content strings of new pages
category	switch to decide, if the pages should be created as category-pages

**Value**

TRUE

---

*get\_action\_token*      *request token for api action as signed in user*

---

**Description**

helper function to request a user action token

**Usage**

`get_action_token(url)`

**Arguments**

`url`                  a URL body

**Value**

a token string

---

*get\_prelogin\_token*      *request token to start client login*

---

**Description**

helper function to request a user login token

**Usage**

`get_prelogin_token(url, user)`

**Arguments**

`url`                  a URL body  
`user`                 a username of a registered user

**Value**

a token string

---

login	<i>wikimedia api user login</i>
-------	---------------------------------

---

### Description

Login to a wikimedia instance to trigger api requests as a registered user. This function only allows the very basic login with username and password. Wikimedia setups that require more sophisticated login methods are not supported.

### Usage

```
login(url, user, pw)
```

### Arguments

url	a URL body
user	a username of a registered user
pw	the password of said user

### Value

TRUE

---

pages_in_category	<i>Retrieves a list of category members.</i>
-------------------	--

---

### Description

wiki\_catpages retrieves a list of pages, subcategories, files or all of the above in a specified category (or series of specified categories)

### Usage

```
pages_in_category(
  language = NULL,
  project = NULL,
  domain = NULL,
  categories,
  properties = c("title", "ids", "sortkey", "sortkeyprefix", "type", "timestamp"),
  type = c("page", "subcat", "file"),
  clean_response = FALSE,
  limit = 50,
  ...
)
```

**Arguments**

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
categories	The names of the categories you want to gather information for.
properties	The properties you want to gather for each member of the category. Options are "title" (the name of the member, including namespace), "id" (the unique numeric identifier of the member), "sortkey" (the hexadecimal key used to sort that member within the category), "sortkeyprefix" (the human-readable sort key), "type" (whether the member is a page, a subcategory or a file) and "timestamp" (when the member was added to the category)
type	The type of member you're interested in returning; options are any permutation of "page" (pages), "subcat" (subcategories) and "file" (files).
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
limit	The maximum number of members to retrieve for each category. Set to 50 by default.
...	further arguments to pass to htr's GET().

**warnings**

Because of the way MediaWiki stores this data, both "the category you asked for doesn't exist" and "the category you asked for exists, but has no members" return in the same way.

**See Also**

[categories\\_in\\_page](#) for finding categories that a specified page is a member of.

**Examples**

```
## Not run:
#Retrieve the pages in the "New Age" category on en.wiki
cats <- pages_in_category("en", "wikipedia", categories = "New Age")

#Retrieve the pages in the "New Age" category on rationalwiki.
rw_cats <- pages_in_category(domain = "rationalwiki.org", categories = "New Age")

## End(Not run)
```

---

page_backlinks	<i>Retrieve a page's backlinks</i>
----------------	------------------------------------

---

### Description

page\_backlinks, when provided with a page title, retrieves backlinks to that page. Output can be filtered to specific namespaces.

### Usage

```
page_backlinks(
  language = NULL,
  project = NULL,
  domain = NULL,
  page,
  limit = 50,
  direction = "ascending",
  namespaces = NULL,
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
page	the title of the page you want the backlinks of.
limit	the number of backlinks to return. Set to 50 (the maximum) by default.
direction	the direction to order the backlinks in, by linking page ID: "ascending" or "descending". Set to "ascending" by default.
namespaces	The namespaces to filter to. By default, backlinks from any namespace are retrieved: alternately, a numeric vector of accepted namespaces (which are described <a href="#">here</a> ) can be provided, and only backlinks from pages within those namespaces will be returned.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

### Warnings

as with [pages\\_in\\_category](#), if the page you are linking to does not exist, an empty list will be returned, without any indication of an error.



**Examples**

```
## Not run:
#Backlink
all_bls <- page_backlinks("en","wikipedia", page = "Aaron Halfaker")

#Namespace-specific backlinks
mainspace_bls <- page_backlinks("en","wikipedia", page = "Aaron Halfaker", namespaces = 0)

## End(Not run)
```

---

page_content	<i>Retrieves MediaWiki page content</i>
--------------	---

---

**Description**

wiki\_page retrieves the DOM of a particular MediaWiki page, as a HTML blob inside a JSON object.

**Usage**

```
page_content(
  language = NULL,
  project = NULL,
  domain = NULL,
  page_name,
  page_id = NULL,
  as_wikitext = FALSE,
  clean_response = FALSE,
  ...
)
```

**Arguments**

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
page_name	The title of the page you want to retrieve
page_id	the pageID of the page you want to retrieve. Set to NULL by default, and an alternative to page_name; if both are provided, page_id will be used.
as_wikitext	whether to retrieve the wikimarkup (TRUE) or the HTML (FALSE). Set to FALSE by default.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

**See Also**

[revision\\_diff](#) for retrieving 'diffs' between revisions, [revision\\_content](#) for retrieving the text of specified revisions.

**Examples**

```
## Not run:
#Content from a Wikimedia project
wp_content <- page_content("en","wikipedia", page_name = "Aaron Halfaker")

#Content by ID
wp_content <- page_content("en", "wikipedia", page_id = 12)

#Content from a non-Wikimedia project
rw_content <- page_content(domain = "rationalwiki.org", page_name = "New Age")

## End(Not run)
```

---

page\_external\_links     *Retrieve a page's links*

---

**Description**

`page_external_links`, when provided with a page title, retrieves external wikilinks from the current revision of that page.

**Usage**

```
page_external_links(
  language = NULL,
  project = NULL,
  domain = NULL,
  page,
  protocol = NULL,
  clean_response = FALSE,
  ...
)
```

**Arguments**

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
page	the title of the page you want the links of.

protocol	limit links to those with certain link protocols. Options are listed in Special:ApiSandbox's <a href="#">elprotocol field</a> .
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

### Examples

```
## Not run:
#Links
external_links <- page_external_links("en","wikipedia", page = "Aaron Halfaker")

#Protocol-specific links
external_http_links <- page_external_links("en","wikipedia",
                                           page = "Aaron Halfaker", protocol = "http")

## End(Not run)
```

---

page_info	<i>Retrieve information about a particular page</i>
-----------	---

---

### Description

page\_info, when provided with a page title, retrieves metadata about that page.

### Usage

```
page_info(
  language = NULL,
  project = NULL,
  domain = NULL,
  page,
  properties = c("protection", "talkid", "url", "displaytitle"),
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
page	the title of the page you want the metadata of.

properties	the properties you'd like to retrieve. Some properties (the pageID, namespace, title, language, length and most recent revision ID, for example) are retrieved by default, whatever is passed to <code>properties</code> : properties that can be explicitly retrieved include the page's protection level ("protection"), the ID of the associated talk page, if applicable ("talkid"), the full, canonical URL ("url"), and the displayed page title ("displaytitle").
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to <code>httr</code> 's GET.

### Examples

```
## Not run:
#Metadata
page_metadata <- page_info("en","wikipedia", page = "Aaron Halfaker")

## End(Not run)
```

---

page\_links                      *Retrieve a page's links*

---

### Description

`page_links`, when provided with a page title, retrieves internal wikilinks from the current revision of that page.

### Usage

```
page_links(
  language = NULL,
  project = NULL,
  domain = NULL,
  page,
  limit = 50,
  direction = "ascending",
  namespaces = NULL,
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with <code>language</code> .

domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
page	the title of the page you want the links of.
limit	the number of links to retrieve. 50 by default; a maximum of 500 is set server-side.
direction	the direction to order the links in, by destination page ID: "ascending" or "descending". Set to "ascending" by default.
namespaces	The namespaces to filter to. By default, links to any namespace are retrieved; alternately, a numeric vector of accepted namespaces (which are described <a href="#">here</a> ) can be provided, and only backlinks from pages within those namespaces will be returned.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

### Examples

```
## Not run:
#Links
links <- page_links("en","wikipedia", page = "Aaron Halfaker")

#Namespace-specific links
mainpage_links <- page_links("en","wikipedia", page = "Aaron Halfaker", namespaces = 0)

## End(Not run)
```

---

parse\_response      *parse\_response: Parse WikipediR responses internally*

---

### Description

Response parser

### Usage

```
parse_response(x)
```

### Arguments

x                      result from a WikipediR query

### Details

Should not be externally used

---

query	<i>base query function</i>
-------	----------------------------

---

**Description**

not designed to be used by anyone except a third-party reuser package, such as WikidataR

**Usage**

```
query(url, out_class, clean_response = FALSE, query_param = list(), ...)
```

**Arguments**

url	a URL body
out_class	the class to set on the output object; used within WikidataR to indicate what response-cleaning method should be applied.
clean_response	whether to clean the response, using the method assigned by out_class, or not.
query_param	query parameters
...	further arguments to httr's GET.

---

random_page	<i>Retrieve the page content of a random MediaWiki page</i>
-------------	---

---

**Description**

wiki\_page retrieves the DOM of a particular MediaWiki page, as a HTML blob inside a JSON object.

**Usage**

```
random_page(
  language = NULL,
  project = NULL,
  domain = NULL,
  namespaces = NULL,
  as_wikitext = FALSE,
  limit = 1,
  clean_response = FALSE,
  ...
)
```

**Arguments**

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
namespaces	The namespaces to consider pages from. By default, pages from any namespace are considered; alternately, a numeric vector of accepted namespaces (which are described <a href="#">here</a> ) can be provided, and only pages within those namespaces will be considered.
as_wikitext	whether to retrieve the wikimarkup (TRUE) or the HTML (FALSE). Set to FALSE by default.
limit	the number of pages to return. 1 by default.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

**See Also**

[page\\_content](#) for retrieving the content of a specific page, [revision\\_diff](#) for retrieving 'diffs' between revisions, [revision\\_content](#) for retrieving the text of specified revisions.

**Examples**

```
## Not run:
#A page from Wikipedia
wp_content <- random_page("en","wikipedia")

#A page from the mainspace on Wikipedia
wp_article_content <- random_page("en","wikipedia", namespaces = 0)

## End(Not run)
```

---

recent\_changes

*Retrieves entries from the RecentChanges feed*

---

**Description**

wiki\_recentchanges retrieves a stream of entries from Special:RecentChanges, with a variety of associated metadata and filtering (of both entries *\*and\** that metadata).

**Usage**

```

recent_changes(
  language = NULL,
  project = NULL,
  domain = NULL,
  properties = c("user", "userid", "comment", "parsedcomment", "flags", "timestamp",
    "title", "ids", "sizes", "redirect", "loginfo", "tags", "sha1"),
  type = c("edit", "external", "new", "log"),
  tag = NULL,
  dir = "newer",
  limit = 50,
  top = FALSE,
  clean_response = FALSE,
  ...
)

```

**Arguments**

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
properties	Properties you're trying to retrieve about each entry, Options include "user" (the username of the person responsible for that entry), "userid" (the userID of said person), "comment" (the edit summary associated with the entry), "parsedcomment" (the same, but parsed, generating HTML from any wikitext in that comment), "flags" (whether the revision was 'minor' or not), "timestamp", "title" (the name of the page the entry affected), "ids" (the page id, along with the old and new revision IDs when applicable) "sizes" (the size, in uncompressed bytes, of the entry, and, in the case of revisions, the size of the edit it displaced), "tags" (any tags associated with the revision) and "loginfo" (applicable only to log entries, and consisting of log ID numbers, log types and actions, and so on) and "sha1" (the SHA-1 hash of the revision text).
type	The type of entry you want to retrieve; can be any permutation of "edit" (edits to existing pages), "external" (external actions that impact on the project - primarily wikidata changes), "new" (the creation of new pages) and "log" (log entries). By default, all of these entry types are included.
tag	Only return items with particular "tags", such as "mobile edit". NULL by default.
dir	Should it go from newest to oldest ("newer"), or oldest to newest ("older")? By default, set to "newer".
limit	The number of entries you'd like to return. By default, set to 50, which is also the maximum number per-request for logged-out users.



top	Should the request only return "top" entries - in other words, the most recent entry on a page? Set to FALSE by default.
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to http's GET.

---

revision_content	<i>Retrieves MediaWiki revisions</i>
------------------	--------------------------------------

---

### Description

Retrieves the content of a provided list of revisions from whichever MediaWiki instance you're querying. Returns as wikimarkup.

### Usage

```
revision_content(
  language = NULL,
  project = NULL,
  domain = NULL,
  revisions,
  properties = c("content", "ids", "flags", "timestamp", "user", "userid", "size",
    "sha1", "contentmodel", "comment", "parsedcomment", "tags"),
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
revisions	The revision IDs of each desired revision.
properties	Properties you're trying to retrieve about that revision, should you want to; options include "ids" (the revision ID of the revision...which is pointless), "flags" (whether the revision was 'minor' or not), "timestamp" (the timestamp of the revision), "user" (the username of the person who made that revision), "userid" (the userID of the person who made the revision), "size" (the size, in uncompressed bytes, of the revision), "sha1" (the SHA-1 hash of the revision text), "contentmodel" (the content model of the page, usually "wikitext"), "comment" (the revision summary associated with the revision), "parsedcomment" (the same, but parsed, generating HTML from any wikitext in that comment), "tags" (any tags associated with the revision) and "flagged" (the revision's status under Flagged Revisions).

clean\_response whether to do some basic sanitising of the resulting data structure.  
 ... further arguments to pass to httr's GET.

### See Also

[revision\\_diff](#) for diffs between revisions, and [page\\_content](#) for the content a specific page currently has.

### Examples

```
## Not run:
#Revision content from a Wikimedia project
wp_content <- revision_content("en","wikipedia", revisions = 552373187)

#Revision content from a non-Wikimedia project
rw_content <- revision_content(domain = "rationalwiki.org", revisions = 88616)

## End(Not run)
```

---

revision_diff	<i>Generates a "diff" between a pair of revisions</i>
---------------	---

---

### Description

revision\_diff generates a diff between two revisions in a MediaWiki page. This is provided as an XML-parsable blob inside the returned JSON object.

### Usage

```
revision_diff(
  language = NULL,
  project = NULL,
  domain = NULL,
  revisions,
  properties = c("ids", "flags", "timestamp", "user", "userid", "size", "sha1",
    "contentmodel", "comment", "parsedcomment", "tags", "flagged"),
  direction,
  clean_response = FALSE,
  ...
)
```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.

domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
revisions	The revision IDs of each "start" revision.
properties	Properties you're trying to retrieve about that revision, should you want to; options include "ids" (the revision ID of the revision...which is pointless), "flags" (whether the revision was 'minor' or not), "timestamp", "user" (the username of the person who made that revision), "userid" (the userID of the person who made the revision), "size" (the size, in uncompressed bytes, of the revision), "sha1" (the SHA-1 hash of the revision text), "contentmodel" (the content model of the page, usually "wikitext"), "comment" (the revision summary associated with the revision), "parsedcomment" (the same, but parsed, generating HTML from any wikitext in that comment), "tags" (any tags associated with the revision) and "flagged" (the revision's status under Flagged Revisions).
direction	The direction you want the diff to go in from the revisionID you have provided. Options are "prev" (compare to the previous revision on that page), "next" (compare to the next revision on that page) and "cur" (compare to the current, extant version of the page).
clean_response	whether to do some basic sanitising of the resulting data structure.
...	further arguments to pass to httr's GET.

## Warnings

MediaWiki's API is deliberately designed to restrict users' ability to make computing-intense requests - such as diff computation. As a result, the API only allows requests for one uncached diff in each request. If you ask for multiple diffs, some uncached and some cached, you will be provided with the cached diffs, one of the uncached diffs, and a warning.

If you're going to be asking for a lot of diffs, some of which may not be cached, it may be more sensible to retrieve the revisions themselves using [revision\\_content](#) and compute the diffs yourself.

## See Also

[page\\_content](#) for retrieving the current content of a specific page, and [revision\\_content](#) for retrieving the text of specific revisions.

## Examples

```
## Not run:
#Wikimedia diff
wp_diff <- revision_diff("en","wikipedia", revisions = 552373187, direction = "next")

#Non-Wikimedia diff
rw_diff <- revision_diff(domain = "rationalwiki.org", revisions = 88616, direction = "next")

## End(Not run)
```

---

user\_contributions      *Retrieve user contributions*

---

### Description

Retrieves metadata associated with the most recent contributions by a specified user.

### Usage

```

user_contributions(
    language = NULL,
    project = NULL,
    domain = NULL,
    username,
    properties = c("ids", "title", "timestamp", "comment", "parsedcomment", "size",
        "sizediff", "flags", "tags"),
    mainspace = FALSE,
    limit = 50,
    clean_response = FALSE,
    ...
)

```

### Arguments

language	The language code of the project you wish to query, if appropriate.
project	The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.
domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
username	The username of the user whose contributions you want to retrieve. Due to limitations at the API end, you can only retrieve edits for one user at a time.
properties	The metadata you want associated with each edit. Potential metadata includes "ids" (the revision ID of the revision, which can be passed into <a href="#">revision_content</a> ), "title" (the name of the page that was edited), "timestamp", "comment" (the edit summary associated with the revision), "parsedcomment" (the same, but parsed, generating HTML from any wikitext in that comment), "size" (the size, in uncompressed bytes, of the edit), "sizediff" (the size delta between this edit, and the last edit to the page), "flags" (whether the revision was 'minor' or not), and "tags" (any tags associated with the revision).
mainspace	A boolean flag; FALSE retrieves all of the most recent contributions, while TRUE limits the retrieved contributions to those in the 'mainspace' - in other words, edits to actual articles. Set to FALSE by default
limit	The number of edits to be retrieved. 50 is the maximum for logged-out API users, and putting in more than 50 will generate a warning.

clean\_response whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.

... further arguments to pass to httr's GET.

### See Also

[user\\_information](#) for information about a specific user (or group of users), and [recent\\_changes](#) for non-user-specific recent actions.

### Examples

```
## Not run:
#Retrieve the timestamps of a user's recent contributions to the English-language Wikipedia
contribs <- user_contributions("en", "wikipedia", username = "Ironholds",
                             properties = "timestamp")

#Retrieve the timestamps of a user's recent contributions to a non-Wikimedia wiki.
rw_contribs <- user_contributions(domain = "rationalwiki.org", username = "David Gerard",
                                 properties = "ids", limit = 1)

## End(Not run)
```

---

user_information	<i>Retrieve user information</i>
------------------	----------------------------------

---

### Description

Retrieves information about a user, or set of users, from the MediaWiki API, including registration date, gender and editcount.

### Usage

```
user_information(
  language = NULL,
  project = NULL,
  domain = NULL,
  user_names,
  properties = c("blockinfo", "groups", "implicitgroups", "rights", "editcount",
                "registration", "emailable", "gender"),
  clean_response = FALSE,
  ...
)
```

### Arguments

language The language code of the project you wish to query, if appropriate.

project The project you wish to query ("wikiquote"), if appropriate. Should be provided in conjunction with language.

domain	as an alternative to a language and project combination, you can also provide a domain ("rationalwiki.org") to the URL constructor, allowing for the querying of non-Wikimedia MediaWiki instances.
user_names	The username(s) of the users you want information on - this should be provided as a vector. There is a hard limit of 50 distinct users per query, set by MediaWiki's API; in the event that you go over this, a warning will be issued and the query will only be performed for the first 50 names in the vector.
properties	The user properties you're interested in. Applicable properties are "blockinfo" (details about the user's block, if they are currently blocked), "groups" (the user groups the user is a member of), "implicitgroups" (groups they are a member of through inheritance, as a result of membership in other groups), "rights" (what permissions their group membership grants them), "editcount" (how many non-deleted edits they have), "registration" (the date when they registered), "emailable" (whether they are contactable through Special:EmailUser) and "gender" (their provided gender).
clean_response	whether to do some basic sanitising of the resulting data structure. Set to FALSE by default.
...	further arguments to pass to httr's GET.

## Warnings

There are a few caveats with the data provided by `user_information`, mostly stemming from historical inconsistencies and peculiarities in MediaWiki.

`groups` and `implicitgroups` gives you the user's permissions and group membership on the project you are querying, not their membership on all projects - while you can find out if "Ironholds" is not a sysop on, say, enwiki, that doesn't mean they aren't a sysop elsewhere - there is no universal, API-accessible user groups listing.

As an extension of the lack of centrality in Wikimedia's infrastructure, `registration` tells you the date their account was created on the wiki you are querying. If they initially registered on that wiki, this is accurate - if they registered on a different wiki, this instead reflects the date and time that they first visited the wiki you're querying while logged-in. For users registered before 2006, when registration logging was introduced, the `registration` value represents not when they first registered, but when their first edit was, since that was used as an estimator for existing accounts when the field was first populated.

## See Also

[user\\_contributions](#) for retrieving recent contributions made by a particular user.

## Examples

```
## Not run:
#Retrieving information from a Wikimedia project
user_info <- user_information("en", "wikipedia", user_names = "David Gerard",
                             properties = "registration")

#Non-Wikimedia projects
user_info <- user_information(domain = "rationalwiki.org", user_names = "David Gerard",
```

```
properties = "registration")  
  
## End(Not run)
```

---

WikipediR

*A client library for MediaWiki's API*

---

### **Description**

This package provides functions for accessing the MediaWiki API, either for Wikimedia projects or any other MediaWiki instance. For more information, see the [vignette](#).

### **See Also**

The [package vignette](#).

# Index

`categories_in_page`, [2](#), [7](#)

`create_page`, [3](#)

`create_pages`, [4](#)

`get_action_token`, [5](#)

`get_prelogin_token`, [5](#)

`login`, [6](#)

`page_backlinks`, [8](#)

`page_content`, [9](#), [15](#), [18](#), [19](#)

`page_external_links`, [10](#)

`page_info`, [11](#)

`page_links`, [12](#)

`pages_in_category`, [3](#), [6](#), [8](#)

`parse_response`, [13](#)

`query`, [14](#)

`random_page`, [14](#)

`recent_changes`, [15](#)

`revision_content`, [10](#), [15](#), [17](#), [19](#), [20](#)

`revision_diff`, [10](#), [15](#), [18](#), [18](#)

`user_contributions`, [20](#), [22](#)

`user_information`, [21](#), [21](#)

WikipediR, [23](#)

WikipediR-package (WikipediR), [23](#)