

Package ‘basetable’

September 12, 2026

Title Fast and Memory-Efficient Base R Table Manipulation

Version 1.3.2

Description A tabular data manipulation, exploration and validation toolkit with a base R-style interface (subset, transform, aggregate, merge, split) and no external computation dependency. Grouping, joins, ordering, filtering, reshaping and delimited-file reading run in a bundled 'C++' engine that uses multiple threads for the heavier operations. Grouped reducers accumulate in compiled code without materialising intermediate columns, so grouped aggregation and counting allocate close to nothing. Results are returned as an ordinary data frame with a light 'basetable' class.

License MIT + file LICENSE

URL <https://github.com/ielbadisy/basetable>

BugReports <https://github.com/ielbadisy/basetable/issues>

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.2.0)

Imports parallel, stats, utils

Suggests bench, data.table, dplyr, ggplot2, knitr, rmarkdown, scales, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

SystemRequirements C++17

NeedsCompilation yes

Author Imad El Badisy [aut, cre]

Maintainer Imad El Badisy <elbadisyimad@gmail.com>

Repository CRAN

Date/Publication 2026-09-12 12:20:02 UTC

Contents

basetable-package	7
adddays	7
addedrows	8
addmonths	8
addweeks	9
addyears	9
aggregate	10
antimerge	10
applyby	11
applycols	12
assertcols	12
assertcomplete	13
assertkey	13
assertnames	14
assertrange	14
assertrows	15
asserttype	15
assertunique	16
assertvalues	16
assert_cols	17
betweendates	17
blanktona	18
btread	18
btwrite	20
cardinality	21
casewhen	22
ceilingdate	22
center	23
changedcols	23
changedrows	24
classes	24
cleannames	25
collapselevels	25
collapsestext	26
collapsevalues	26
colnames	27
commonnames	27
compare	28
compareschema	28
completegrid	29
constants	29
containstext	30
convertcols	30
count	31
countmatch	31
crossmerge	32

cumavg	32
cumcount	33
cumedist	33
datediff	34
dateseq	34
day	35
denserank	35
describe	36
difference	36
diffrows	37
dims	37
drop	38
duplicatekeys	38
duplicatenames	39
duplicaterows	39
emptycols	40
emptyrows	40
endswith	41
equaldata	41
equalrows	42
expandlevels	42
expandrows	43
extract	43
extractall	44
extractbetween	44
extractint	45
extractnum	45
fillboth	46
filldown	46
fillup	47
firstby	47
firstcols	48
firstrows	48
floordate	49
foldr	49
freq	50
headtail	50
hour	51
intersectrows	51
invalidrows	52
invalidvalues	52
isalpha	53
isalphanumeric	53
isblank	54
isemail	54
isintegertext	55
isnumerictext	55
isurl	56

joinrelationship	56
jointext	57
keepmissing	57
lagvalue	58
lastby	58
lastcols	59
lastrows	59
leadvalue	60
left	60
locate	61
locateall	61
lower	62
lump	62
map	63
matchedkeys	63
matchestext	64
merge	64
middle	65
minute	65
missingindicator	66
missingness	66
missingrows	67
month	67
move	68
naif	68
nato	69
natoblack	69
ncols	70
nearestmerge	70
nearesttext	71
nonequimerge	71
normalizeencoding	72
normalizeunicode	72
nrows	73
omitmissing	73
orderrows	74
outofrange	74
overlapmerge	75
padcenter	75
padleft	76
padright	76
parsecurrency	77
parsedate	77
parsedatetime	78
parsefailures	78
parseint	79
parselogical	79
parsenum	80

parsepercent	80
percentchange	81
percentrank	81
pick	82
preview	82
profile	83
propcount	83
quantilegroup	84
quarter	84
rangemerge	85
rbindfill	85
recode	86
removeaccents	87
removeall	87
removedrows	88
removeduplicates	88
removetext	89
renamecols	89
renamewith	90
reorderlevels	90
repairnames	91
replaceall	91
replacecols	92
replacetext	92
replacevalues	93
replacewhere	93
rescale	94
reverse	94
right	95
rollapply	95
rollingmerge	96
rollmax	97
rollmean	97
rollmedian	98
rollmin	99
rollprod	100
rollsd	100
rollsum	101
rollvar	102
rounddate	103
rowall	103
rowany	104
rowapply	104
rowcount	105
rowfirst	105
rowlast	106
rowmax	106
rowmin	107

rownames	107
rownumber	108
sameschema	108
samplefrac	109
samplerows	109
second	110
semimerge	110
sentencecase	111
separate	111
setthreads	112
similartext	112
split	113
splitfirst	113
splitlast	114
splittext	114
squish	115
stack	115
standardize	116
startswith	116
subset	117
summaries	118
summarytab	118
textdist	119
textlen	120
titlecase	120
tolong	121
towide	121
transliterate	122
transpose	123
traverse	123
trim	124
truncate	124
types	125
unionrows	125
uniquerows	126
uniques	126
unite	127
unmatchedkeys	127
unstack	128
updatemerge	128
upper	129
week	129
weekday	130
winsorize	130
within	131
year	131
yearday	132

basetable-package	<i>Base-Faithful Tabular Data Tools</i>
-------------------	---

Description

The **basetable** package provides a compact set of base-style data manipulation and exploratory data analysis helpers backed by a native C++ table engine.

Details

Core design rules:

- exported data verbs take the main data object as their first argument
- grouping is explicit with `by =`
- outputs are plain data frames or lists in most cases
- interfaces are intended to work naturally in nested calls and native `|>` pipelines

adddays	<i>Add days to a date</i>
---------	---------------------------

Description

Add days to a date

Usage

```
adddays(x, n)
```

Arguments

x	An atomic vector.
n	Integer count.

Value

A Date vector.

addedrows

Rows present in new but not in old

Description

Rows present in new but not in old

Usage

```
addedrows(old, new, by = NULL)
```

Arguments

old	Baseline data.frame ("before" state).
new	Updated data.frame ("after" state), or replacement values when used for value substitution.
by	Character vector of column names identifying groups or join keys.

Value

The added rows.

addmonths

Add months to a date

Description

Add months to a date

Usage

```
addmonths(x, n, invalid = c("previous", "next", "missing", "error"))
```

Arguments

x	An atomic vector.
n	Integer count.
invalid	How to handle an invalid resulting date.

Value

A Date vector.

addweeks	<i>Add weeks to a date</i>
----------	----------------------------

Description

Add weeks to a date

Usage

```
addweeks(x, n)
```

Arguments

x	An atomic vector.
n	Integer count.

Value

A Date vector.

addyears	<i>Add years to a date</i>
----------	----------------------------

Description

Add years to a date

Usage

```
addyears(x, n, invalid = c("previous", "next", "missing", "error"))
```

Arguments

x	An atomic vector.
n	Integer count.
invalid	How to handle an invalid resulting date.

Value

A Date vector.

 aggregate

Aggregate values by group

Description

Compute grouped summaries for one or more value columns. When data is a single file path, the file is scanned once and only the grouping and value fields are extracted, without materialising the other columns.

Usage

```
aggregate(data, by, value = NULL, fun, ..., na.rm = FALSE, sort = TRUE)
```

Arguments

data	A data frame, or a single path to a delimited text file for the fused one-pass file mode.
by	Character vector of grouping columns.
value	Optional character vector of value columns to summarize.
fun	Summary function applied to each value column. In file mode this is one or more of "sum", "mean", "var", "sd", "min", "max", "n" and defaults to "sum".
...	Additional arguments passed to fun; in file mode, reader options such as where, delim, n_threads.
na.rm	Whether to remove missing values before summarizing (defaults to TRUE in file mode).
sort	Whether to sort output rows by group.

Value

A basetable containing one row per group.

 antimerge

Anti-join two tables

Description

Keep rows in x whose keys do not exist in y.

Usage

```
antimerge(x, y, by)
```

Arguments

x, y	Data frames or data tables to compare.
by	Character vector of join columns.

Value

A basetable containing rows from x without matches in y.

applyby	<i>Apply a function to each group</i>
---------	---------------------------------------

Description

Apply a function to each group

Usage

```
applyby(data, by, fun, ..., bind = FALSE, id = ".group")
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.
fun	Function applied to each element, column, or group.
...	Additional arguments (unused, or passed through depending on the function).
bind	Combine the per-group results into a single table.
id	Optional name for a source identifier column.

Value

A list of per-group results, or a combined table when bind = TRUE.

applycols	<i>Apply a function to selected columns</i>
-----------	---

Description

Apply a function to selected columns

Usage

```
applycols(data, cols, fun, ...)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
fun	Function applied to each element, column, or group.
...	Additional arguments (unused, or passed through depending on the function).

Value

data with the selected columns transformed.

assertcols	<i>Assert that columns exist (alias)</i>
------------	--

Description

Assert that columns exist (alias)

Usage

```
assertcols(data, cols)
```

Arguments

data	A data.frame.
cols	Character vector of column names.

Value

See [assert_cols\(\)](#).

assertcomplete	<i>Assert that there are no missing values</i>
----------------	--

Description

Assert that there are no missing values

Usage

```
assertcomplete(data, cols = NULL)
```

Arguments

data	A data.frame.
cols	Character vector of column names.

Value

data, invisibly, if the assertion passes.

assertkey	<i>Assert that a key is unique (alias)</i>
-----------	--

Description

Assert that a key is unique (alias)

Usage

```
assertkey(data, by)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.

Value

See [assert_key\(\)](#).

assertnames	<i>Assert that required column names are present</i>
-------------	--

Description

Assert that required column names are present

Usage

```
assertnames(data, names)
```

Arguments

data	A data.frame.
names	Required column names.

Value

data, invisibly, if the assertion passes.

assertrange	<i>Assert that a column falls within a numeric range</i>
-------------	--

Description

Assert that a column falls within a numeric range

Usage

```
assertrange(data, column, lower, upper)
```

Arguments

data	A data.frame.
column	Name of a single column.
lower	Lower bound.
upper	Upper bound.

Value

data, invisibly, if the assertion passes.

assertrows	<i>Assert that a row-wise condition holds for every row</i>
------------	---

Description

Assert that a row-wise condition holds for every row

Usage

```
assertrows(data, condition)
```

Arguments

data	A data.frame.
condition	A logical expression evaluated in the context of data.

Value

data, invisibly, if the assertion passes.

asserttype	<i>Assert that a column has an expected class</i>
------------	---

Description

Assert that a column has an expected class

Usage

```
asserttype(data, column, class)
```

Arguments

data	A data.frame.
column	Name of a single column.
class	Class name to check against.

Value

data, invisibly, if the assertion passes.

assertunique	<i>Assert that selected columns are unique</i>
--------------	--

Description

Assert that selected columns are unique

Usage

```
assertunique(data, cols)
```

Arguments

data	A data.frame.
cols	Character vector of column names.

Value

data, invisibly, if the assertion passes.

assertvalues	<i>Assert that a column only contains allowed values</i>
--------------	--

Description

Assert that a column only contains allowed values

Usage

```
assertvalues(data, column, allowed)
```

Arguments

data	A data.frame.
column	Name of a single column.
allowed	Vector of permitted values.

Value

data, invisibly, if the assertion passes.

assert_cols*Validation and schema helpers*

Description

Low-level helpers for validating columns and keys or comparing schemas.

Usage

```
assert_cols(data, cols)
```

```
assert_key(data, by)
```

```
common_names(x, y)
```

```
duplicated_keys(data, by)
```

Arguments

data, x, y A data.frame.

cols, by Character vectors naming columns.

Value

assert_cols() and assert_key() return their input invisibly. common_names() returns a character vector. duplicated_keys() returns a data frame of duplicated key combinations.

Examples

```
common_names(mtcars, iris)
assert_cols(mtcars, c("mpg", "hp"))
duplicated_keys(data.frame(id = c(1, 1, 2)), "id")
```

betweendates*Test whether a date falls within a range*

Description

Test whether a date falls within a range

Usage

```
betweendates(x, start, end)
```

Arguments

- x An atomic vector.
- start Start bound (inclusive).
- end End bound (inclusive).

Value

A logical vector.

blanktona	<i>Recode blank strings to NA</i>
-----------	-----------------------------------

Description

Recode blank strings to NA

Usage

blanktona(x)

Arguments

- x An atomic vector.

Value

x with blanks replaced by NA.

btread	<i>Read a delimited text file</i>
--------	-----------------------------------

Description

A from-scratch delimited-file reader written in C++: the file is memory mapped, scanned once for row boundaries (RFC 4180 quoting), type-guessed from a bounded sample, and materialised into typed vectors. Numeric columns are filled by a thread pool; character columns are built on the R thread.

Usage

```

bthread(
  file,
  delim = NULL,
  header = TRUE,
  col_names = NULL,
  col_types = NULL,
  col_select = NULL,
  na = c("NA", ""),
  quote = "\"",
  comment = "",
  trim_ws = FALSE,
  skip = 0,
  n_max = Inf,
  guess_max = 10000,
  lazy = FALSE,
  n_threads = bt_default_threads(),
  as = c("data.frame", "basetable")
)

```

Arguments

file	Path to a delimited text file. .gz inputs are decompressed to a temporary file first.
delim	Field delimiter. NULL (default) sniffs the first line for one of , \t ; and a space.
header	Logical; does the first row hold column names?
col_names	Optional character vector of names, used only when header = FALSE. Defaults to V1, V2, ...
col_types	NULL to guess, or a character vector of "logical", "integer", "double", "character", "skip", "guess". Length 1 is recycled; otherwise it must have one entry per column.
col_select	Optional integer positions or character names of the columns to keep. Other columns are not parsed.
na	Character vector of strings to read as NA.
quote	Quoting character.
comment	Lines beginning with this one-character string are skipped ("" disables).
trim_ws	Logical; strip leading/trailing spaces and tabs from unquoted fields.
skip	Number of raw lines to discard before reading.
n_max	Maximum number of data rows to read (Inf for all).
guess_max	Number of rows sampled for type guessing.
lazy	Logical; return numeric columns as lazily-parsed ALTREP vectors.
n_threads	Number of worker threads for the eager numeric fill.
as	Return "data.frame" (default) or "basetable".

Details

With `lazy = TRUE` the integer and double columns are returned as ALTREP vectors that parse their column only the first time it is touched, which makes "read a few columns from a wide file" close to free.

Value

A data.frame.

Examples

```
p <- tempfile(fileext = ".csv")
write.csv(head(iris), p, row.names = FALSE)
bthead(p)
```

btwrite

Write a data frame to a delimited text file

Description

A threaded C++ writer: each column is resolved to a plain C array on the R thread, then disjoint row ranges are formatted into private buffers and flushed in order.

Usage

```
btwrite(
  x,
  file,
  delim = ",",
  na = "NA",
  col_names = TRUE,
  quote = "\"",
  digits = 15,
  append = FALSE,
  n_threads = bt_default_threads()
)
```

Arguments

<code>x</code>	A data.frame.
<code>file</code>	Output path.
<code>delim</code>	Field delimiter.
<code>na</code>	String to write for NA.
<code>col_names</code>	Logical; write a header row?
<code>quote</code>	Quoting character; a field is quoted only if it contains the delimiter, the quote character, or a newline.

digits	Significant digits for double columns (passed to %g).
append	Logical; append to file instead of overwriting (no header is written when appending).
n_threads	Number of worker threads.

Value

file, invisibly.

Examples

```
p <- tempfile(fileext = ".csv")
btwrite(head(iris), p)
btread(p)
```

cardinality	<i>Distinct-value count (or proportion) per column</i>
-------------	--

Description

Distinct-value count (or proportion) per column

Usage

```
cardinality(data, cols, prop = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
prop	Return the proportion of distinct values instead of the count.

Value

A named numeric vector.

casewhen	<i>Multi-branch selection by condition</i>
----------	--

Description

For each position, take the label of the first condition that is TRUE there. Conditions are a named list of equal-length logical vectors, in the same shape as `collapsevalues()`'s groups: the name of an element is the value used where that element is the first TRUE. Positions matching no condition get default. NA in a condition counts as not matching.

Usage

```
casewhen(conditions, default = NA)
```

Arguments

conditions	A named list of equal-length logical vectors. Each name is the value returned where its vector is the first TRUE.
default	Value for positions where no condition holds. Default NA.

Value

A vector as long as the conditions, holding matched labels and default elsewhere.

Examples

```
x <- c(-3, 0, 4, 25)
casewhen(list(neg = x < 0, low = x < 10), default = "high")
```

ceilingdate	<i>Round a date up to a unit</i>
-------------	----------------------------------

Description

Round a date up to a unit

Usage

```
ceilingdate(x, unit = c("day", "week", "month", "year"))
```

Arguments

x	An atomic vector.
unit	Time unit to round to.

Value

A Date vector.

center	<i>Center a vector at its mean</i>
--------	------------------------------------

Description

Center a vector at its mean

Usage

```
center(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A centered numeric vector.

changedcols	<i>Compare the columns of two tables</i>
-------------	--

Description

Compare the columns of two tables

Usage

```
changedcols(old, new)
```

Arguments

old	Baseline data.frame ("before" state).
new	Updated data.frame ("after" state), or replacement values when used for value substitution.

Value

See [compareschema\(\)](#).

changedrows	<i>Rows whose key appears in both tables</i>
-------------	--

Description

Rows whose key appears in both tables

Usage

```
changedrows(old, new, by = NULL)
```

Arguments

old	Baseline data.frame ("before" state).
new	Updated data.frame ("after" state), or replacement values when used for value substitution.
by	Character vector of column names identifying groups or join keys.

Value

The matched rows from both tables, suffixed .old/.new.

classes	<i>Column classes</i>
---------	-----------------------

Description

Column classes

Usage

```
classes(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A basetable with one row per column giving its class.

cleannames	<i>Clean column names to a unique, syntactic form</i>
------------	---

Description

Clean column names to a unique, syntactic form

Usage

```
cleannames(data)
```

Arguments

data	A data.frame.
------	---------------

Value

data with cleaned column names.

collapselevels	<i>Collapse factor levels into named groups</i>
----------------	---

Description

Collapse factor levels into named groups

Usage

```
collapselevels(x, groups)
```

Arguments

x	An atomic vector.
groups	Named list mapping a replacement label to the values it should collapse.

Value

A character vector with levels collapsed.

collapsetext	<i>Collapse a vector into a single string</i>
--------------	---

Description

Collapse a vector into a single string

Usage

```
collapsetext(x, sep = "")
```

Arguments

x	An atomic vector.
sep	Separator string.

Value

A single character string.

collapsevalues	<i>Collapse values into named groups</i>
----------------	--

Description

Collapse values into named groups

Usage

```
collapsevalues(x, groups)
```

Arguments

x	An atomic vector.
groups	Named list mapping a replacement label to the values it should collapse.

Value

x with values replaced by their group label.

colnames	<i>Column names</i>
----------	---------------------

Description

Column names

Usage

colnames(data)

Arguments

data A data.frame.

Value

A character vector of column names.

commonnames	<i>Column names shared by two tables</i>
-------------	--

Description

Column names shared by two tables

Usage

commonnames(x, y)

Arguments

x An atomic vector.
y An atomic vector, data.frame, or basetable, depending on the function.

Value

See [common_names\(\)](#).

compare	<i>Compare tables</i>
---------	-----------------------

Description

Compare dimensions, names, types, missingness, and key overlap for two tables.

Usage

```
compare(x, y, by = NULL)
```

Arguments

x, y	Data frames or data tables to compare.
by	Optional key columns for overlap checks.

Value

A list of comparison tables.

compareschema	<i>Compare the schemas of two tables</i>
---------------	--

Description

Compare the schemas of two tables

Usage

```
compareschema(x, y)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.

Value

A basetable describing shared and differing columns/types.

completegrid	<i>Complete a table grid</i>
--------------	------------------------------

Description

Create all combinations of selected columns and merge them back to the input.

Usage

```
completegrid(data, cols, fill = list())
```

Arguments

data	A data frame or data table.
cols	Character vector of columns to complete across.
fill	Named list of values used to fill missing cells.

Value

A basetable containing the completed grid.

constants	<i>Columns with a single distinct non-missing value</i>
-----------	---

Description

Columns with a single distinct non-missing value

Usage

```
constants(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A character vector of constant column names.

containstext	<i>Test for a pattern match anywhere in the string</i>
--------------	--

Description

Test for a pattern match anywhere in the string

Usage

```
containstext(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A logical vector.

convertcols	<i>Convert selected columns with a function</i>
-------------	---

Description

Convert selected columns with a function

Usage

```
convertcols(data, cols, fun, ...)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
fun	Function applied to each element, column, or group.
...	Additional arguments (unused, or passed through depending on the function).

Value

data with the selected columns converted.

count	<i>Count rows by group</i>
-------	----------------------------

Description

Count rows in a table by one or more grouping columns.

Usage

```
count(data, by, sort = TRUE, name = "n", ...)
```

Arguments

data	A data frame, or a single path to a delimited text file for the fused one-pass file mode.
by	Character vector of grouping columns.
sort	Whether to sort by descending counts.
name	Name of the count column.
...	In file mode, reader options such as where, delim.

Value

A basetable with one row per group.

countmatch	<i>Count pattern matches per string</i>
------------	---

Description

Count pattern matches per string

Usage

```
countmatch(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

An integer vector.

crossmerge	<i>Cartesian join two tables</i>
------------	----------------------------------

Description

Return every combination of rows from x and y.

Usage

```
crossmerge(x, y)
```

Arguments

x, y Data frames or data tables to combine.

Value

A basetable containing the Cartesian product of the rows.

cumavg	<i>Cumulative mean</i>
--------	------------------------

Description

Cumulative mean

Usage

```
cumavg(x)
```

Arguments

x An atomic vector.

Value

A numeric vector.

cumcount	<i>Cumulative row counter</i>
----------	-------------------------------

Description

Cumulative row counter

Usage

cumcount(x)

Arguments

x An atomic vector.

Value

An integer sequence along x.

cumedist	<i>Cumulative empirical distribution</i>
----------	--

Description

Cumulative empirical distribution

Usage

cumedist(x)

Arguments

x An atomic vector.

Value

A numeric vector.

datediff	<i>Difference between two dates</i>
----------	-------------------------------------

Description

Difference between two dates

Usage

```
datediff(x, y, units = "days")
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
units	Unit used to express the difference.

Value

A numeric vector of differences.

dateseq	<i>Sequence of dates</i>
---------	--------------------------

Description

Sequence of dates

Usage

```
dateseq(from, to, by = "day", length.out = NULL)
```

Arguments

from	Start date.
to	End date, or target range for rescaling.
by	Character vector of column names identifying groups or join keys.
length.out	Desired sequence length.

Value

A Date vector.

day	<i>Extract the day of month</i>
-----	---------------------------------

Description

Extract the day of month

Usage

day(x)

Arguments

x An atomic vector.

Value

An integer vector.

denserank	<i>Dense rank of a vector</i>
-----------	-------------------------------

Description

Dense rank of a vector

Usage

denserank(x)

Arguments

x An atomic vector.

Value

An integer vector of dense ranks.

describe	<i>Column descriptions</i>
----------	----------------------------

Description

Summarize a table with basic counts, missingness, distinct values, and descriptive statistics.

Usage

```
describe(data, cols = NULL, top_n = 3)
```

Arguments

data	A data frame or data table.
cols	Optional character vector of columns to describe.
top_n	Number of most frequent values to show for non-numeric columns.

Value

A basetable with one row per column.

difference	<i>Lagged difference</i>
------------	--------------------------

Description

Lagged difference

Usage

```
difference(x, lag = 1L)
```

Arguments

x	An atomic vector.
lag	Lag used for the difference.

Value

A numeric vector of differences.

diffrows	<i>Set difference of rows</i>
----------	-------------------------------

Description

Set difference of rows

Usage

```
diffrows(x, y, by = NULL)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
by	Character vector of column names identifying groups or join keys.

Value

Rows of x absent from y.

dims	<i>Table dimensions</i>
------	-------------------------

Description

Return the number of rows and columns in a table.

Usage

```
dims(data)
```

Arguments

data	A data frame or data table.
------	-----------------------------

Value

A one-row data frame with the row and column counts.

drop	<i>Drop columns</i>
------	---------------------

Description

Drop columns by name.

Usage

```
drop(data, cols)
```

Arguments

data	A data frame or data table.
cols	Character vector of column names to remove.

Value

A basetable with the selected columns removed.

duplicatekeys	<i>Duplicated key combinations</i>
---------------	------------------------------------

Description

Duplicated key combinations

Usage

```
duplicatekeys(data, by)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.

Value

See [duplicated_keys\(\)](#).

duplicatenames	<i>Duplicated column names</i>
----------------	--------------------------------

Description

Duplicated column names

Usage

duplicatenames(data)

Arguments

data A data.frame.

Value

A character vector of the duplicated names.

duplicaterows	<i>Rows involved in a duplicate</i>
---------------	-------------------------------------

Description

Rows involved in a duplicate

Usage

duplicaterows(data)

Arguments

data A data.frame.

Value

A data.frame of the duplicated rows.

emptycols	<i>Columns that are entirely blank or missing</i>
-----------	---

Description

Columns that are entirely blank or missing

Usage

```
emptycols(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A character vector of column names.

emptyrows	<i>Rows that are entirely blank or missing</i>
-----------	--

Description

Rows that are entirely blank or missing

Usage

```
emptyrows(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A data.frame of the fully blank rows.

endswith	<i>Test whether strings end with a pattern</i>
----------	--

Description

Test whether strings end with a pattern

Usage

```
endswith(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A logical vector.

equaldata	<i>Compare two tables for equality</i>
-----------	--

Description

Compare two tables for equality

Usage

```
equaldata(  
  x,  
  y,  
  ignoreorder = FALSE,  
  ignorerownames = TRUE,  
  tolerance = sqrt(.Machine$double.eps)  
)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
ignoreorder	Ignore row order when comparing.
ignorerownames	Ignore row names when comparing.
tolerance	Numeric join/comparison tolerance.

Value

A single logical value.

equalrows

Compare two tables' rows for equality

Description

Compare two tables' rows for equality

Usage

```
equalrows(x, y, by = NULL)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
by	Character vector of column names identifying groups or join keys.

Value

A single logical value.

expandlevels

Add levels to a factor

Description

Add levels to a factor

Usage

```
expandlevels(x, levels)
```

Arguments

x	An atomic vector.
levels	Character vector of factor levels.

Value

A factor including the additional levels.

expandrows	<i>Repeat rows in a table</i>
------------	-------------------------------

Description

Repeat each row of a table according to a count vector.

Usage

```
expandrows(data, times)
```

Arguments

data	A data frame or data table.
times	A scalar or row-wise count vector giving repetitions.

Value

A basetable with repeated rows.

extract	<i>Extract the first pattern match</i>
---------	--

Description

Extract the first pattern match

Usage

```
extract(x, pattern, ...)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when <code>fixed = TRUE</code>).
...	Additional arguments (unused, or passed through depending on the function).

Value

A character vector of matches.

extractall	<i>Extract all pattern matches</i>
------------	------------------------------------

Description

Extract all pattern matches

Usage

```
extractall(x, pattern, ...)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
...	Additional arguments (unused, or passed through depending on the function).

Value

A list of character vectors of matches.

extractbetween	<i>Extract text between two markers</i>
----------------	---

Description

Extract text between two markers

Usage

```
extractbetween(x, left, right)
```

Arguments

x	An atomic vector.
left	Left marker.
right	Right marker.

Value

A character vector.

extractint	<i>Extract an integer value from text</i>
------------	---

Description

Extract an integer value from text

Usage

extractint(x)

Arguments

x An atomic vector.

Value

An integer vector.

extractnum	<i>Extract a numeric value from text</i>
------------	--

Description

Extract a numeric value from text

Usage

extractnum(x)

Arguments

x An atomic vector.

Value

A numeric vector.

fillboth	<i>Fill missing values both forward and backward within groups</i>
----------	--

Description

Fill missing values both forward and backward within groups

Usage

```
fillboth(data, cols, by = NULL)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
by	Character vector of column names identifying groups or join keys.

Value

data with cols filled in both directions.

filldown	<i>Fill missing values downward</i>
----------	-------------------------------------

Description

Fill missing values in selected columns using the last observed value.

Usage

```
filldown(data, cols, by = NULL)
```

Arguments

data	A data frame or data table.
cols	Character vector of columns to fill.
by	Optional grouping columns.

Value

A basetable with missing values filled downward.

fillup	<i>Fill missing values upward</i>
--------	-----------------------------------

Description

Fill missing values in selected columns using the next observed value.

Usage

```
fillup(data, cols, by = NULL)
```

Arguments

data	A data frame or data table.
cols	Character vector of columns to fill.
by	Optional grouping columns.

Value

A basetable with missing values filled upward.

firstby	<i>First row within each group</i>
---------	------------------------------------

Description

First row within each group

Usage

```
firstby(data, by, order = NULL)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.
order	Optional column(s) used to break ties before picking first/last rows.

Value

One row per group.

<code>firstcols</code>	<i>Move columns to the front</i>
------------------------	----------------------------------

Description

Move columns to the front

Usage

```
firstcols(data, cols)
```

Arguments

- `data` A data.frame.
- `cols` Character vector of column names.

Value

data with cols moved first.

<code>firstrows</code>	<i>First n rows</i>
------------------------	---------------------

Description

First n rows

Usage

```
firstrows(data, n = 1L)
```

Arguments

- `data` A data.frame.
- `n` Integer count.

Value

The first n rows of data.

floordate	<i>Round a date down to a unit</i>
-----------	------------------------------------

Description

Round a date down to a unit

Usage

```
floordate(x, unit = c("day", "week", "month", "year"))
```

Arguments

x	An atomic vector.
unit	Time unit to round to.

Value

A Date vector.

foldr	<i>Fold a vector or list from the right</i>
-------	---

Description

Reduce `.x` with the two-argument function `.f`, associating from the right, a thin wrapper around `base::Reduce()` with `right = TRUE`. With `.accumulate = TRUE` the intermediate results are returned as well.

Usage

```
foldr(.x, .f, .init = NULL, .accumulate = FALSE, .simplify = TRUE)
```

Arguments

.x	A vector or list.
.f	A two-argument reducing function.
.init	Optional initial value.
.accumulate	Return intermediate accumulated values.
.simplify	Simplify accumulated results when possible.

Value

The folded value, or accumulated values when `.accumulate = TRUE`.

Examples

```
foldr(1:4, ``)  
foldr(letters[1:4], paste0, .accumulate = TRUE)
```

freq	<i>Frequency table</i>
------	------------------------

Description

Count the occurrences of values in a column, optionally within groups.

Usage

```
freq(data, column, by = NULL, prop = FALSE, sort = TRUE, ...)
```

Arguments

data	A data frame, or a single path to a delimited text file. In file mode the second argument is taken as the grouping column(s).
column	Name of the column to tabulate.
by	Optional grouping column or columns.
prop	Whether to include proportions.
sort	Whether to sort rows by descending frequency.
...	In file mode, reader options such as where, delim.

Value

A basetable containing frequencies, and proportions when requested.

headtail	<i>Head and tail rows</i>
----------	---------------------------

Description

Return the first and last ‘n’ rows of a table.

Usage

```
headtail(data, n = 3)
```

Arguments

data	A data frame or data table.
n	Number of rows to show from the start and end.

Value

A basetable containing the selected rows.

hour	<i>Extract the hour</i>
------	-------------------------

Description

Extract the hour

Usage

hour(x)

Arguments

x An atomic vector.

Value

An integer vector.

intersectrows	<i>Set intersection of rows</i>
---------------	---------------------------------

Description

Set intersection of rows

Usage

intersectrows(x, y, by = NULL)

Arguments

x An atomic vector.
y An atomic vector, data.frame, or basetable, depending on the function.
by Character vector of column names identifying groups or join keys.

Value

Rows of x also present in y.

invalidrows	<i>Rows that fail a condition</i>
-------------	-----------------------------------

Description

Rows that fail a condition

Usage

```
invalidrows(data, condition)
```

Arguments

data	A data.frame.
condition	A logical expression evaluated in the context of data.

Value

The rows of data for which condition is not TRUE.

invalidvalues	<i>Rows whose value is not in the allowed set</i>
---------------	---

Description

Rows whose value is not in the allowed set

Usage

```
invalidvalues(data, column, allowed)
```

Arguments

data	A data.frame.
column	Name of a single column.
allowed	Vector of permitted values.

Value

The rows of data with disallowed values.

isalpha	<i>Test for alphabetic-only strings</i>
---------	---

Description

Test for alphabetic-only strings

Usage

isalpha(x)

Arguments

x An atomic vector.

Value

A logical vector.

isalphanumeric	<i>Test for alphanumeric-only strings</i>
----------------	---

Description

Test for alphanumeric-only strings

Usage

isalphanumeric(x)

Arguments

x An atomic vector.

Value

A logical vector.

isblank	<i>Test for blank (missing or empty) values</i>
---------	---

Description

Test for blank (missing or empty) values

Usage

```
isblank(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A logical vector.

isemail	<i>Test whether text looks like an email address</i>
---------	--

Description

Test whether text looks like an email address

Usage

```
isemail(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A logical vector.

isintegertext	<i>Test whether text looks like an integer</i>
---------------	--

Description

Test whether text looks like an integer

Usage

```
isintegertext(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A logical vector.

isnumerictext	<i>Test whether text looks numeric</i>
---------------	--

Description

Test whether text looks numeric

Usage

```
isnumerictext(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A logical vector.

isurl	<i>Test whether text looks like a URL</i>
-------	---

Description

Test whether text looks like a URL

Usage

```
isurl(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A logical vector.

joinrelationship	<i>Cardinality of a join key relationship</i>
------------------	---

Description

Cardinality of a join key relationship

Usage

```
joinrelationship(x, y, by)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
by	Character vector of column names identifying groups or join keys.

Value

One of "one-to-one", "one-to-many", "many-to-one", "many-to-many".

jointext	<i>Concatenate values element-wise</i>
----------	--

Description

Concatenate values element-wise

Usage

```
jointext(...)
```

Arguments

... Additional arguments (unused, or passed through depending on the function).

Value

A character vector.

keepmissing	<i>Keep rows with missing values</i>
-------------	--------------------------------------

Description

Return rows where selected columns are missing or blank.

Usage

```
keepmissing(data, cols = NULL, mode = c("any", "all"))
```

Arguments

data	A data frame or data table.
cols	Optional character vector of columns to inspect.
mode	Whether any or all selected columns must be missing.

Value

A basetable containing the matching rows.

lagvalue	<i>Lag a vector</i>
----------	---------------------

Description

Lag a vector

Usage

```
lagvalue(x, n = 1L, default = NA)
```

Arguments

x	An atomic vector.
n	Integer count.
default	Value used to fill positions with no lagged observation.

Value

x shifted forward by n positions.

lastby	<i>Last row within each group</i>
--------	-----------------------------------

Description

Last row within each group

Usage

```
lastby(data, by, order = NULL)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.
order	Optional column(s) used to break ties before picking first/last rows.

Value

One row per group.

lastcols	<i>Move columns to the back</i>
----------	---------------------------------

Description

Move columns to the back

Usage

```
lastcols(data, cols)
```

Arguments

data	A data.frame.
cols	Character vector of column names.

Value

data with cols moved last.

lastrows	<i>Last n rows</i>
----------	--------------------

Description

Last n rows

Usage

```
lastrows(data, n = 1L)
```

Arguments

data	A data.frame.
n	Integer count.

Value

The last n rows of data.

leadvalue	<i>Lead a vector</i>
-----------	----------------------

Description

Lead a vector

Usage

```
leadvalue(x, n = 1L, default = NA)
```

Arguments

- x An atomic vector.
- n Integer count.
- default Value used to fill positions with no leading observation.

Value

x shifted backward by n positions.

left	<i>First n characters</i>
------	---------------------------

Description

First n characters

Usage

```
left(x, n)
```

Arguments

- x An atomic vector.
- n Integer count.

Value

A character vector.

locate	<i>Position of the first pattern match</i>
--------	--

Description

Position of the first pattern match

Usage

```
locate(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

An integer vector of match positions (see [regexpr\(\)](#)).

locateall	<i>Positions of all pattern matches</i>
-----------	---

Description

Positions of all pattern matches

Usage

```
locateall(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A list of match positions (see [gregexpr\(\)](#)).

lower	<i>Convert to lower case</i>
-------	------------------------------

Description

Convert to lower case

Usage

lower(x)

Arguments

x An atomic vector.

Value

A lower-case character vector.

lump	<i>Lump infrequent values into "Other"</i>
------	--

Description

Lump infrequent values into "Other"

Usage

lump(x, n = 5, other = "Other")

Arguments

x An atomic vector.
n Integer count.
other Label used for values outside the top n.

Value

A character vector.

map	<i>Map over vectors and lists</i>
-----	-----------------------------------

Description

A small base-R-style mapping helper with no external dependency: apply `.f` to each element of `.x` and return the results in a list, like `base::lapply()` with a friendlier argument name.

Usage

```
map(.x, .f, ...)
```

Arguments

<code>.x</code>	A vector or list.
<code>.f</code>	A function or function name.
<code>...</code>	Additional arguments passed to <code>.f</code> .

Value

`map()` returns a list.

Examples

```
map(1:3, function(x) x + 1)
```

matchedkeys	<i>Rows of x whose key is present in y</i>
-------------	--

Description

Rows of `x` whose key is present in `y`

Usage

```
matchedkeys(x, y, by)
```

Arguments

<code>x</code>	An atomic vector.
<code>y</code>	An atomic vector, data.frame, or basetable, depending on the function.
<code>by</code>	Character vector of column names identifying groups or join keys.

Value

Rows of `x` whose key is present in `y`.

matchestext	<i>Test for a full-string pattern match</i>
-------------	---

Description

Test for a full-string pattern match

Usage

```
matchestext(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A logical vector.

merge	<i>Merge two tables</i>
-------	-------------------------

Description

Merge two tables using shared keys.

Usage

```
merge(x, y, by = NULL, all = FALSE, all.x = all, all.y = all,
      sort = FALSE, suffixes = c(".x", ".y"))
```

Arguments

x, y	Data frames or data tables to merge.
by	Optional character vector of join columns.
all, all.x, all.y	Controls for keeping unmatched rows.
sort	Whether to sort the result.
suffixes	Suffixes used for overlapping column names.

Value

A basetable containing the merged rows.

middle	<i>Substring between two positions</i>
--------	--

Description

Substring between two positions

Usage

```
middle(x, start, end)
```

Arguments

x	An atomic vector.
start	Start bound (inclusive).
end	End bound (inclusive).

Value

A character vector.

minute	<i>Extract the minute</i>
--------	---------------------------

Description

Extract the minute

Usage

```
minute(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

An integer vector.

missingindicator	<i>Add missingness indicators</i>
------------------	-----------------------------------

Description

Append logical indicators showing whether selected columns are missing or blank.

Usage

```
missingindicator(data, cols = NULL, prefix = "missing_")
```

Arguments

data	A data frame or data table.
cols	Optional character vector of columns to inspect.
prefix	Prefix used for the added indicator columns.

Value

A basetable with logical missingness indicator columns appended.

missingness	<i>Summarize missing values by column or row</i>
-------------	--

Description

Summarize missing values by column or row

Usage

```
missingness(data, margin = c("column", "row"))
```

Arguments

data	A data.frame.
margin	Summarize missingness "column"-wise (the default) or "row"-wise.

Value

A basetable with one row per column (or per row) describing the count and proportion of missing values.

missingrows	<i>Return rows with missing values</i>
-------------	--

Description

Return rows where selected columns are missing or blank.

Usage

```
missingrows(data, cols = NULL, mode = c("any", "all"))
```

Arguments

data	A data frame or data table.
cols	Optional character vector of columns to inspect.
mode	Whether any or all selected columns must be missing.

Value

A basetable containing the matching rows.

month	<i>Extract the month</i>
-------	--------------------------

Description

Extract the month

Usage

```
month(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

An integer vector.

move	<i>Move columns before or after another column</i>
------	--

Description

Move columns before or after another column

Usage

```
move(data, cols, before = NULL, after = NULL)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
before	Column identifying where to insert cols before.
after	Column identifying where to insert cols after.

Value

data with columns reordered.

naif	<i>Recode matching values to NA</i>
------	-------------------------------------

Description

Recode matching values to NA

Usage

```
naif(x, values)
```

Arguments

x	An atomic vector.
values	Vector or list of replacement values.

Value

x with matches replaced by NA.

nato	<i>Replace NA with a value</i>
------	--------------------------------

Description

Replace NA with a value

Usage

```
nato(x, value)
```

Arguments

x	An atomic vector.
value	Value to test, assign, or match against.

Value

x with missing values replaced.

natoblank	<i>Replace NA with an empty string</i>
-----------	--

Description

Replace NA with an empty string

Usage

```
natoblank(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

x with missing values replaced by "".

ncols	<i>Number of columns</i>
-------	--------------------------

Description

Return the number of columns in a table.

Usage

```
ncols(data)
```

Arguments

data	A data frame or data table.
------	-----------------------------

Value

An integer scalar.

nearestmerge	<i>Nearest-key join</i>
--------------	-------------------------

Description

Nearest-key join

Usage

```
nearestmerge(x, y, by, tolerance = Inf)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
by	Character vector of column names identifying groups or join keys.
tolerance	Numeric join/comparison tolerance.

Value

See [rollingmerge\(\)](#).

nearesttext	<i>Nearest string match</i>
-------------	-----------------------------

Description

Nearest string match

Usage

```
nearesttext(x, choices)
```

Arguments

x	An atomic vector.
choices	Candidate strings to match against.

Value

A character vector of nearest matches.

nonequimerge	<i>Merge two tables using non-equi (inequality) conditions</i>
--------------	--

Description

Unlike a plain [equi-merge](#), `nonequimerge()` supports inequality conditions between columns of `x` and `y` (for example, matching each `x` row to every `y` row whose date range contains `x`'s date), in addition to any exact-match columns in `by`.

Usage

```
nonequimerge(x, y, by, ...)
```

Arguments

x, y	Data frames or data tables to join.
by	Character vector of join conditions. A plain column name (present in both <code>x</code> and <code>y</code>) is matched exactly; an entry containing a comparison operator, written as " <code>xcol<op>ycol</code> " (e.g. " <code>date>=start_date</code> ", " <code>date<=end_date</code> "), is matched as an inequality between <code>x</code> 's <code>xcol</code> and <code>y</code> 's <code>ycol</code> . This uses " <code>col>=other</code> " style comparison strings.
...	Currently ignored; reserved for future join (e.g. <code>mult</code> , <code>roll</code>).

Value

A basetable with one row per matching x/y pair (an inner join: rows of x with no matching y row are dropped).

Examples

```
x <- data.frame(id = 1, date = as.Date("2024-01-15"))
y <- data.frame(
  id = 1,
  start_date = as.Date(c("2024-01-01", "2024-02-01")),
  end_date = as.Date(c("2024-01-31", "2024-02-28")),
  period = c("Jan", "Feb")
)
nonequimerge(x, y, by = c("id", "date>=start_date", "date<=end_date"))
```

normalizeencoding	<i>Normalize text encoding to UTF-8</i>
-------------------	---

Description

Normalize text encoding to UTF-8

Usage

```
normalizeencoding(x)
```

Arguments

x An atomic vector.

Value

A character vector.

normalizeunicode	<i>Normalize Unicode text</i>
------------------	-------------------------------

Description

Normalize Unicode text

Usage

```
normalizeunicode(x)
```

Arguments

x An atomic vector.

Value

A character vector (currently returned unchanged).

nrows	<i>Number of rows</i>
-------	-----------------------

Description

Return the number of rows in a table.

Usage

```
nrows(data)
```

Arguments

data A data frame or data table.

Value

An integer scalar.

omitmissing	<i>Drop rows with missing values</i>
-------------	--------------------------------------

Description

Drop rows where selected columns are missing or blank.

Usage

```
omitmissing(data, cols = NULL, mode = c("any", "all"))
```

Arguments

data A data frame or data table.
cols Optional character vector of columns to inspect.
mode Whether any or all selected columns must be missing before a row is dropped.

Value

A basetable without the omitted rows.

orderrows	<i>Order rows by one or more columns</i>
-----------	--

Description

Order rows by one or more columns

Usage

```
orderrows(data, by, decreasing = FALSE, na.last = TRUE)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.
decreasing	Sort in decreasing order.
na.last	Placement of missing values when sorting.

Value

data sorted by by.

outofrange	<i>Rows whose value falls outside a range</i>
------------	---

Description

Rows whose value falls outside a range

Usage

```
outofrange(data, column, lower, upper)
```

Arguments

data	A data.frame.
column	Name of a single column.
lower	Lower bound.
upper	Upper bound.

Value

The rows of data outside [lower, upper].

overlapmerge	<i>Merge tables on overlapping intervals</i>
--------------	--

Description

Join tables by overlapping interval ranges.

Usage

```
overlapmerge(x, y, startx, endx, starty, endy, by = NULL)
```

Arguments

x, y	Data frames or data tables to join.
startx, endx	Interval bounds in x.
starty, endy	Interval bounds in y.
by	Optional character vector of exact-match grouping columns.

Value

A basetable containing the overlap matches.

padcenter	<i>Pad text on both sides</i>
-----------	-------------------------------

Description

Pad text on both sides

Usage

```
padcenter(x, width, pad = " ")
```

Arguments

x	An atomic vector.
width	Target width, in characters or rolling-window size depending on the function.
pad	Padding character.

Value

A character vector padded to width.

padleft	<i>Pad text on the left</i>
---------	-----------------------------

Description

Pad text on the left

Usage

```
padleft(x, width, pad = " ")
```

Arguments

x	An atomic vector.
width	Target width, in characters or rolling-window size depending on the function.
pad	Padding character.

Value

A character vector padded to width.

padright	<i>Pad text on the right</i>
----------	------------------------------

Description

Pad text on the right

Usage

```
padright(x, width, pad = " ")
```

Arguments

x	An atomic vector.
width	Target width, in characters or rolling-window size depending on the function.
pad	Padding character.

Value

A character vector padded to width.

parsecurrency	<i>Parse a currency string as a number</i>
---------------	--

Description

Parse a currency string as a number

Usage

```
parsecurrency(x, strict = FALSE)
```

Arguments

x	An atomic vector.
strict	Raise an error if any non-missing value fails to parse.

Value

A numeric vector.

parsedate	<i>Parse text as dates, trying multiple formats</i>
-----------	---

Description

Parse text as dates, trying multiple formats

Usage

```
parsedate(x, formats, tz = "UTC", strict = FALSE)
```

Arguments

x	An atomic vector.
formats	Candidate format strings tried in order.
tz	Time zone used when parsing.
strict	Raise an error if any non-missing value fails to parse.

Value

A Date vector.

parsedatetime	<i>Parse text as date-times, trying multiple formats</i>
---------------	--

Description

Parse text as date-times, trying multiple formats

Usage

```
parsedatetime(x, formats, tz = "UTC", strict = FALSE)
```

Arguments

x	An atomic vector.
formats	Candidate format strings tried in order.
tz	Time zone used when parsing.
strict	Raise an error if any non-missing value fails to parse.

Value

A POSIXct vector.

parsefailures	<i>Rows where parsing failed</i>
---------------	----------------------------------

Description

Rows where parsing failed

Usage

```
parsefailures(x, fun, ...)
```

Arguments

x	An atomic vector.
fun	Function applied to each element, column, or group.
...	Additional arguments (unused, or passed through depending on the function).

Value

A basetable of the failed indices and values.

parseint	<i>Parse text as integers</i>
----------	-------------------------------

Description

Parse text as integers

Usage

```
parseint(x, na = character(), strict = FALSE)
```

Arguments

x	An atomic vector.
na	Values treated as missing before parsing.
strict	Raise an error if any non-missing value fails to parse.

Value

An integer vector.

parselogical	<i>Parse text as logicals</i>
--------------	-------------------------------

Description

Parse text as logicals

Usage

```
parselogical(x, na = character(), strict = FALSE)
```

Arguments

x	An atomic vector.
na	Values treated as missing before parsing.
strict	Raise an error if any non-missing value fails to parse.

Value

A logical vector.

parsenum	<i>Parse text as numbers</i>
----------	------------------------------

Description

Parse text as numbers

Usage

```
parsenum(x, decimal = ".", grouping = ",", na = character(), strict = FALSE)
```

Arguments

x	An atomic vector.
decimal	Decimal mark used in the input strings.
grouping	Thousands-grouping mark used in the input strings.
na	Values treated as missing before parsing.
strict	Raise an error if any non-missing value fails to parse.

Value

A numeric vector.

parsepercent	<i>Parse a percentage string as a number</i>
--------------	--

Description

Parse a percentage string as a number

Usage

```
parsepercent(x, strict = FALSE)
```

Arguments

x	An atomic vector.
strict	Raise an error if any non-missing value fails to parse.

Value

A numeric vector.

percentchange	<i>Period-over-period percent change</i>
---------------	--

Description

Period-over-period percent change

Usage

percentchange(x)

Arguments

x An atomic vector.

Value

A numeric vector of percent changes.

percentrank	<i>Percentile rank of a vector</i>
-------------	------------------------------------

Description

Percentile rank of a vector

Usage

percentrank(x)

Arguments

x An atomic vector.

Value

A numeric vector of percentile ranks in $[0, 1]$.

pick	<i>Select columns</i>
------	-----------------------

Description

Select columns by name.

Usage

```
pick(data, cols)
```

Arguments

data	A data frame or data table.
cols	Character vector of column names.

Value

A basetable containing the selected columns.

preview	<i>Compact table preview</i>
---------	------------------------------

Description

Print a concise preview of a table with its row and column counts and a short summary of each variable.

Usage

```
preview(data, width = getOption("width"))
```

Arguments

data	A data frame or data table.
width	Maximum line width for printed output.

Value

The input data, invisibly.

profile	<i>Compact variable profile</i>
---------	---------------------------------

Description

Return a compact profile table for the variables in a data set.

Usage

```
profile(data, cols = NULL, top_n = 3)
```

Arguments

data	A data frame or data table.
cols	Optional character vector of columns to profile.
top_n	Number of most frequent values to show for non-numeric columns.

Value

A basetable with one row per column.

propcount	<i>Grouped counts with proportions</i>
-----------	--

Description

Grouped counts with proportions

Usage

```
propcount(data, by, margin = NULL)
```

Arguments

data	A data.frame.
by	Character vector of column names identifying groups or join keys.
margin	Column(s) defining the totals used to compute proportions.

Value

A basetable of counts (and proportions when margin is supplied).

quantilegroup	<i>Bin a vector into quantile groups</i>
---------------	--

Description

Bin a vector into quantile groups

Usage

```
quantilegroup(x, n = 5)
```

Arguments

- x An atomic vector.
- n Integer count.

Value

A factor of quantile bins.

quarter	<i>Extract the calendar quarter</i>
---------	-------------------------------------

Description

Extract the calendar quarter

Usage

```
quarter(x)
```

Arguments

- x An atomic vector.

Value

An integer vector.

rangemerge	<i>Merge two tables by a range condition</i>
------------	--

Description

For each row of *x*, keep the row(s) of *y* whose value column falls between *x*'s lower and upper bounds (inclusive), within the exact-match by key.

Usage

```
rangemerge(x, y, by, lower, upper, value)
```

Arguments

<i>x, y</i>	Data frames or data tables to join.
<i>by</i>	Character vector of exact-match join columns, present in both <i>x</i> and <i>y</i> .
<i>lower, upper</i>	Single columns in <i>x</i> describing the inclusive range bounds to test against.
<i>value</i>	Single column in <i>y</i> whose value is tested against each matching <i>x</i> row's [<i>lower</i> , <i>upper</i>] range.

Value

A basetable with one row per *x* row for each *y* row whose value falls within [*lower*, *upper*] (matching on *by*); an *x* row with no matching *y* row appears once with NA for *y*'s columns.

Examples

```
x <- data.frame(id = c(1, 1, 2), lower = c(0, 0, 0), upper = c(10, 10, 20))
y <- data.frame(id = c(1, 1, 2), val = c(5, 15, 5), label = c("a", "b", "c"))
rangemerge(x, y, by = "id", lower = "lower", upper = "upper", value = "val")
```

rbindfill	<i>Row-bind tables, filling missing columns</i>
-----------	---

Description

Combine data frames by row, filling columns that are missing from some inputs with NA.

Usage

```
rbindfill(..., id = NULL, fill = TRUE, typeconflict = c("error", "coerce"))
```

Arguments

<code>...</code>	Data frames to combine, or a single list of them.
<code>id</code>	Optional name for a source identifier column recording which input each row came from.
<code>fill</code>	Fill missing columns with NA instead of erroring when inputs have different columns.
<code>typeconflict</code>	How to handle a column whose type differs across inputs. "error" (the default) stops with a message naming the column and the conflicting types before any coercion happens. "coerce" skips the check and allows ordinary vector coercion while binding.

Value

A combined basetable.

recode	<i>Recode values by lookup (alias)</i>
--------	--

Description

Recode values by lookup (alias)

Usage

```
recode(x, old, new)
```

Arguments

<code>x</code>	An atomic vector.
<code>old</code>	Baseline data.frame ("before" state).
<code>new</code>	Updated data.frame ("after" state), or replacement values when used for value substitution.

Value

See [replacevalues\(\)](#).

removeaccents	<i>Strip accents from text</i>
---------------	--------------------------------

Description

Fold accented Latin letters to their unaccented ASCII form ("café" -> "cafe"), following ICU's Latin-ASCII mapping: covers the Latin-1 Supplement and Latin Extended-A blocks, plus a few common extras (ß -> "ss", Æ -> "AE", Romanian ș/ț). Characters with no mapping, including non-Latin scripts, pass through unchanged. No Unicode library dependency.

Usage

```
removeaccents(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A character vector the same length as x.

See Also

[transliterate\(\)](#) for Greek and Cyrillic as well.

Examples

```
removeaccents(c("café", "naïve", "Zürich", "Kraków"))
```

removeall	<i>Remove text matching a pattern (alias)</i>
-----------	---

Description

Remove text matching a pattern (alias)

Usage

```
removeall(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A character vector.

removedrows	<i>Rows present in old but not in new</i>
-------------	---

Description

Rows present in old but not in new

Usage

```
removedrows(old, new, by = NULL)
```

Arguments

- old Baseline data.frame ("before" state).
- new Updated data.frame ("after" state), or replacement values when used for value substitution.
- by Character vector of column names identifying groups or join keys.

Value

The removed rows.

removeduplicates	<i>Remove duplicate rows, optionally by key</i>
------------------	---

Description

Remove duplicate rows, optionally by key

Usage

```
removeduplicates(data, by = NULL, keep = c("first", "last", "none"))
```

Arguments

- data A data.frame.
- by Character vector of column names identifying groups or join keys.
- keep Which duplicate to keep.

Value

data with duplicates removed.

removetext	<i>Remove text matching a pattern</i>
------------	---------------------------------------

Description

Remove text matching a pattern

Usage

```
removetext(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A character vector.

renamecols	<i>Rename columns</i>
------------	-----------------------

Description

Rename columns using new = old pairs. Old column names may be supplied as bare names or character strings.

Usage

```
renamecols(data, ...)
```

Arguments

data	A data.frame.
...	Named rename expressions, as new = old.

Value

data with the named columns renamed.

renamewith	<i>Rename columns with a function</i>
------------	---------------------------------------

Description

Rename columns with a function

Usage

```
renamewith(data, cols, fun)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
fun	Function applied to each element, column, or group.

Value

data with the selected columns renamed.

reorderlevels	<i>Reorder factor levels</i>
---------------	------------------------------

Description

Reorder factor levels

Usage

```
reorderlevels(x, by)
```

Arguments

x	An atomic vector.
by	Character vector of column names identifying groups or join keys.

Value

A factor with reordered levels.

repairnames	<i>Repair column names</i>
-------------	----------------------------

Description

Repair column names

Usage

```
repairnames(data, method = c("unique", "universal", "minimal"))
```

Arguments

data	A data.frame.
method	Cleaning strategy to apply to names.

Value

data with repaired column names.

replaceall	<i>Recode values by lookup (alias)</i>
------------	--

Description

Recode values by lookup (alias)

Usage

```
replaceall(x, old, new)
```

Arguments

x	An atomic vector.
old	Existing value(s) to replace.
new	Replacement value(s) matching old by position.

Value

See [replacevalues\(\)](#).

replacecols	<i>Replace selected columns with new values</i>
-------------	---

Description

Replace selected columns with new values

Usage

```
replacecols(data, cols, values)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
values	Vector or list of replacement values.

Value

data with the selected columns replaced.

replacetext	<i>Replace a pattern with replacement text</i>
-------------	--

Description

Replace a pattern with replacement text

Usage

```
replacetext(x, pattern, replacement, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
replacement	Replacement text.
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A character vector.

replacevalues	<i>Recode values by lookup</i>
---------------	--------------------------------

Description

Recode values by lookup

Usage

```
replacevalues(x, old, new)
```

Arguments

x	An atomic vector.
old	Baseline data.frame ("before" state).
new	Updated data.frame ("after" state), or replacement values when used for value substitution.

Value

x with matched values replaced.

replacewhere	<i>Replace values in selected columns where a condition holds</i>
--------------	---

Description

Replace values in selected columns where a condition holds

Usage

```
replacewhere(data, condition, cols, value)
```

Arguments

data	A data.frame.
condition	A logical expression evaluated in the context of data.
cols	Character vector of column names.
value	Value to test, assign, or match against.

Value

data with matching values replaced.

rescale	<i>Rescale a vector to a new range</i>
---------	--

Description

Rescale a vector to a new range

Usage

```
rescale(x, to = c(0, 1))
```

Arguments

x	An atomic vector.
to	End date, or target range for rescaling.

Value

A rescaled numeric vector.

reverse	<i>Reverse row order</i>
---------	--------------------------

Description

Reverse row order

Usage

```
reverse(data)
```

Arguments

data	A data.frame.
------	---------------

Value

data with rows in reverse order.

right	<i>Last n characters</i>
-------	--------------------------

Description

Last n characters

Usage

```
right(x, n)
```

Arguments

x	An atomic vector.
n	Integer count.

Value

A character vector.

rollapply	<i>Rolling window apply</i>
-----------	-----------------------------

Description

Rolling window apply

Usage

```
rollapply(  
  x,  
  width,  
  FUN,  
  ...,  
  align = c("right", "left", "center"),  
  fill = NA,  
  partial = FALSE  
)
```

Arguments

x	An atomic vector.
width	Target width, in characters or rolling-window size depending on the function.
FUN	Function applied to each rolling window.
...	Additional arguments (unused, or passed through depending on the function).
align	Alignment of the rolling window relative to each position.
fill	Value used for positions where no window/result is available.
partial	Allow partial windows at the boundaries.

Value

A vector with one result per window.

rollingmerge	<i>Rolling join two tables</i>
--------------	--------------------------------

Description

Join tables using a rolling match on the last key column.

Usage

```
rollingmerge(x, y, by, direction = c("backward", "forward", "nearest"),
  tolerance = Inf)
```

Arguments

x, y	Data frames or data tables to join.
by	Character vector of join columns. The last column is treated as the rolling key.
direction	Rolling direction: backward, forward, or nearest.
tolerance	Maximum distance allowed for rolling matches.

Value

A basetable with rows from x joined to nearest matches in y.

rollmax	<i>Rolling maximum</i>
---------	------------------------

Description

Rolling maximum

Usage

```
rollmax(  
  x,  
  width,  
  align = c("right", "left", "center"),  
  fill = NA,  
  partial = FALSE,  
  na.rm = FALSE  
)
```

Arguments

x	An atomic vector.
width	Target width, in characters or rolling-window size depending on the function.
align	Alignment of the rolling window relative to each position.
fill	Value used for positions where no window/result is available.
partial	Allow partial windows at the boundaries.
na.rm	Drop missing values before computing the result.

Value

A numeric vector of rolling maximums.

rollmean	<i>Rolling mean</i>
----------	---------------------

Description

Rolling mean

Usage

```
rollmean(
  x,
  width,
  align = c("right", "left", "center"),
  fill = NA,
  partial = FALSE,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling means.

rollmedian	<i>Rolling median</i>
------------	-----------------------

Description

Rolling median

Usage

```
rollmedian(
  x,
  width,
  align = c("right", "left", "center"),
  fill = NA,
  partial = FALSE,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling medians.

<code>rollmin</code>	<i>Rolling minimum</i>
----------------------	------------------------

Description

Rolling minimum

Usage

```
rollmin(
  x,
  width,
  align = c("right", "left", "center"),
  fill = NA,
  partial = FALSE,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling minimums.

rollprod	<i>Rolling product</i>
----------	------------------------

Description

Rolling product

Usage

```
rollprod(  
  x,  
  width,  
  align = c("right", "left", "center"),  
  fill = NA,  
  partial = FALSE,  
  na.rm = FALSE  
)
```

Arguments

- | | |
|---------|---|
| x | An atomic vector. |
| width | Target width, in characters or rolling-window size depending on the function. |
| align | Alignment of the rolling window relative to each position. |
| fill | Value used for positions where no window/result is available. |
| partial | Allow partial windows at the boundaries. |
| na.rm | Drop missing values before computing the result. |

Value

A numeric vector of rolling products.

rollsd	<i>Rolling standard deviation</i>
--------	-----------------------------------

Description

Rolling standard deviation

Usage

```
rollsd(
  x,
  width,
  align = c("right", "left", "center"),
  fill = NA,
  partial = FALSE,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling standard deviations.

rollsum	<i>Rolling sum</i>
---------	--------------------

Description

Rolling sum

Usage

```
rollsum(
  x,
  width,
  align = c("right", "left", "center"),
  fill = NA,
  partial = FALSE,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling sums.

<code>rollvar</code>	<i>Rolling variance</i>
----------------------	-------------------------

Description

Rolling variance

Usage

```
rollvar(  
  x,  
  width,  
  align = c("right", "left", "center"),  
  fill = NA,  
  partial = FALSE,  
  na.rm = FALSE  
)
```

Arguments

<code>x</code>	An atomic vector.
<code>width</code>	Target width, in characters or rolling-window size depending on the function.
<code>align</code>	Alignment of the rolling window relative to each position.
<code>fill</code>	Value used for positions where no window/result is available.
<code>partial</code>	Allow partial windows at the boundaries.
<code>na.rm</code>	Drop missing values before computing the result.

Value

A numeric vector of rolling variances.

rounddate	<i>Round a date to the nearest unit</i>
-----------	---

Description

Round a date to the nearest unit

Usage

```
rounddate(x, unit = c("day", "week", "month", "year"))
```

Arguments

x	An atomic vector.
unit	Time unit to round to.

Value

A Date vector.

rowall	<i>Row-wise all() across columns</i>
--------	--------------------------------------

Description

Row-wise all() across columns

Usage

```
rowall(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A logical vector.

rowany	<i>Row-wise any() across columns</i>
--------	--------------------------------------

Description

Row-wise any() across columns

Usage

```
rowany(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A logical vector.

rowapply	<i>Apply a function row-wise</i>
----------	----------------------------------

Description

Apply a function row-wise

Usage

```
rowapply(data, cols = NULL, fun, ...)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
fun	Function applied to each element, column, or group.
...	Additional arguments (unused, or passed through depending on the function).

Value

The result of fun applied to each row.

rowcount	<i>Count matches of a value across columns, per row</i>
----------	---

Description

Count matches of a value across columns, per row

Usage

```
rowcount(data, cols = NULL, value = TRUE, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
value	Value to test, assign, or match against.
na.rm	Drop missing values before computing the result.

Value

An integer vector.

rowfirst	<i>First non-missing value across columns, per row</i>
----------	--

Description

First non-missing value across columns, per row

Usage

```
rowfirst(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A vector of first values.

rowlast	<i>Last non-missing value across columns, per row</i>
---------	---

Description

Last non-missing value across columns, per row

Usage

```
rowlast(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A vector of last values.

rowmax	<i>Row-wise maximum across columns</i>
--------	--

Description

Row-wise maximum across columns

Usage

```
rowmax(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A numeric vector of row maximums.

rowmin	<i>Row-wise minimum across columns</i>
--------	--

Description

Row-wise minimum across columns

Usage

```
rowmin(data, cols = NULL, na.rm = FALSE)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
na.rm	Drop missing values before computing the result.

Value

A numeric vector of row minimums.

rownames	<i>Row names</i>
----------	------------------

Description

Row names

Usage

```
rownames(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A character vector of row names.

rownumber	<i>Row position</i>
-----------	---------------------

Description

Row position

Usage

rownumber(x)

Arguments

x An atomic vector.

Value

An integer sequence along x.

sameschema	<i>Test whether two tables share the same column names</i>
------------	--

Description

Test whether two tables share the same column names

Usage

sameschema(x, y)

Arguments

x An atomic vector.
y An atomic vector, data.frame, or basetable, depending on the function.

Value

A single logical value.

samplefrac	<i>Sample a fraction of rows without replacement</i>
------------	--

Description

Sample a fraction of rows without replacement

Usage

```
samplefrac(data, frac, by = NULL)
```

Arguments

data	A data.frame.
frac	Fraction of rows to sample.
by	Optional character vector of grouping columns; sample frac of each group (rounded up). Sampled rows are returned in their original order.

Value

A random sample of rows.

samplerows	<i>Sample n rows without replacement</i>
------------	--

Description

Sample n rows without replacement

Usage

```
samplerows(data, n, by = NULL)
```

Arguments

data	A data.frame.
n	Integer count.
by	Optional character vector of grouping columns; sample n rows within each group (capped at the group size). Sampled rows are returned in their original order.

Value

A random sample of n rows.

second	<i>Extract the second</i>
--------	---------------------------

Description

Extract the second

Usage

second(x)

Arguments

x An atomic vector.

Value

An integer vector.

semimerge	<i>Semi-join two tables</i>
-----------	-----------------------------

Description

Keep rows in x whose keys exist in y.

Usage

semimerge(x, y, by)

Arguments

x, y Data frames or data tables to compare.
by Character vector of join columns.

Value

A basetable containing rows from x with matches in y.

sentencecase	<i>Convert to sentence case</i>
--------------	---------------------------------

Description

Convert to sentence case

Usage

```
sentencecase(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A sentence-case character vector.

separate	<i>Split one column into several</i>
----------	--------------------------------------

Description

Split one column into several

Usage

```
separate(  
  data,  
  column,  
  into,  
  sep,  
  remove = TRUE,  
  extra = c("warn", "drop", "merge"),  
  fill = c("warn", "left", "right")  
)
```

Arguments

data	A data.frame.
column	Name of a single column.
into	Names of the columns produced by splitting.
sep	Separator string.
remove	Drop the source column(s) after the operation.
extra	How to handle extra pieces beyond into.
fill	Value used for positions where no window/result is available.

Value

data with column split into into.

setthreads	<i>Set basetable thread count for the session</i>
------------	---

Description

Controls the default thread count used by basetable’s native reader and writer when a verb does not receive n_threads explicitly.

Usage

```
setthreads(  
  threads = NULL,  
  restore_after_fork = NULL,  
  percent = NULL,  
  throttle = NULL  
)
```

Arguments

- threads Integer thread count, or NULL to reread environment settings.
- restore_after_fork Ignored; kept for API compatibility.
- percent Percentage of detected logical CPUs to use.
- throttle Ignored; kept for API compatibility.

Value

The previous thread count.

similartext	<i>Nearest string match (alias)</i>
-------------	-------------------------------------

Description

Nearest string match (alias)

Usage

```
similartext(x, choices)
```

Arguments

x An atomic vector.
choices Candidate strings to match against.

Value

See [nearesttext\(\)](#).

split	<i>Split a table by groups</i>
-------	--------------------------------

Description

Split a table into pieces by one or more grouping columns.

Usage

```
split(data, by, drop = FALSE, keep.by = TRUE)
```

Arguments

data A data frame or data table.
by Character vector of grouping columns.
drop Whether to drop empty groups.
keep.by Whether to keep grouping columns in each piece.

Value

A named list of basetables.

splitfirst	<i>First piece after splitting on a separator</i>
------------	---

Description

First piece after splitting on a separator

Usage

```
splitfirst(x, sep, fixed = FALSE)
```

Arguments

x	An atomic vector.
sep	Separator string.
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A character vector.

splitlast	<i>Last piece after splitting on a separator</i>
-----------	--

Description

Last piece after splitting on a separator

Usage

```
splitlast(x, sep, fixed = FALSE)
```

Arguments

x	An atomic vector.
sep	Separator string.
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A character vector.

splittest	<i>Split text on a separator</i>
-----------	----------------------------------

Description

Split text on a separator

Usage

```
splittest(x, sep, fixed = FALSE)
```

Arguments

x	An atomic vector.
sep	Separator string.
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A list of character vectors.

squish	<i>Trim and collapse internal whitespace</i>
--------	--

Description

Trim and collapse internal whitespace

Usage

```
squish(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A cleaned character vector.

stack	<i>Stack columns</i>
-------	----------------------

Description

Convert selected columns into long format with an indicator column.

Usage

```
stack(data, select = NULL, drop = FALSE)
```

Arguments

data	A data frame or data table.
select	Optional character vector of columns to stack.
drop	Whether to drop rows with missing values.

Value

A basetable with a stacked value column.

standardize	<i>Standardize a vector to mean 0, SD 1</i>
-------------	---

Description

Standardize a vector to mean 0, SD 1

Usage

```
standardize(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A standardized numeric vector.

startswith	<i>Test whether strings start with a pattern</i>
------------	--

Description

Test whether strings start with a pattern

Usage

```
startswith(x, pattern, fixed = FALSE)
```

Arguments

x	An atomic vector.
pattern	A regular expression (or fixed string when fixed = TRUE).
fixed	Use fixed (non-regex) matching instead of regular expressions.

Value

A logical vector.

subset

Core data manipulation operations

Description

Base-faithful table manipulation helpers built around explicit arguments, returning a `basetable`. See [aggregate](#), [count](#), [drop](#), [merge](#), [move](#), [orderrows](#), [pick](#), [renamecols](#), [split](#), [stack](#), [summaries](#), [uniquerows](#), [unstack](#), and [within](#) for the remaining core verbs, each documented on its own page.

Usage

```
subset(data, subset = NULL, select = NULL, drop = FALSE, by = NULL)
```

```
transform(data, ..., .keep = TRUE, by = NULL)
```

```
reshape(data, ..., direction)
```

Arguments

<code>data</code>	A <code>data.frame</code> .
<code>subset</code>	A base-style expression evaluated against columns.
<code>select, by</code>	Character vectors naming columns. For <code>subset</code> , by names optional grouping columns: the subset expression is then evaluated within every group, so aggregate references in it (<code>mean(x)</code> , <code>max(x)</code> , ...) are per group; kept rows are returned in their original order. For <code>transform</code> , by names optional grouping columns and each expression in <code>...</code> is evaluated within every group (e.g. <code>cumsum(x)</code> or <code>x - mean(x)</code> computed per group), so the result still has one row per input row. Use summaries for one row per group instead.
<code>drop, .keep</code>	Control flags.
<code>...</code>	Additional expressions or arguments passed through to helpers.
<code>direction</code>	Additional operation-specific controls.

Value

Most functions return a `basetable`.

Examples

```
subset(mtcars, cyl == 6, select = c("mpg", "hp"))
subset(mtcars, mpg > mean(mpg), by = "cyl")
transform(mtcars, power = hp / wt)
transform(mtcars, dev_mpg = mpg - mean(mpg), by = "cyl")
```

summaries	<i>Named grouped summaries</i>
-----------	--------------------------------

Description

Compute multiple named summary expressions, optionally by group.

Usage

```
summaries(data, by = NULL, ...)
```

Arguments

- data A data frame or data table.
- by Optional grouping columns.
- ... Named summary expressions.

Value

A basetable containing the requested summaries.

summarytab	<i>Table 1-style descriptive summary</i>
------------	--

Description

Build a publication-style summary table of one or more variables, optionally stratified by a grouping column, in the manner of a clinical "Table 1".

Usage

```
summarytab(  
  data,  
  vars = NULL,  
  by = NULL,  
  overall = TRUE,  
  p_value = FALSE,  
  digits = 1  
)
```

Arguments

data	A data.frame.
vars	Character vector of variables to summarize. Defaults to every column other than by.
by	Optional single column name used to stratify the summary.
overall	Include an "Overall" column alongside the by-group columns.
p_value	Include a column of between-group p-values. Requires by.
digits	Number of decimal places used when formatting numbers.

Value

A basetable with one row per variable (or variable level), and one column per stratum plus Overall/p_value as requested.

textdist	<i>Pairwise string distances</i>
----------	----------------------------------

Description

Pairwise string distances

Usage

```
textdist(x, y)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.

Value

A numeric distance matrix (see `utils::adist()`).

<code>textlen</code>	<i>Character length</i>
----------------------	-------------------------

Description

Character length

Usage

`textlen(x)`

Arguments

`x` An atomic vector.

Value

An integer vector of character counts.

<code>titlecase</code>	<i>Convert to title case</i>
------------------------	------------------------------

Description

Convert to title case

Usage

`titlecase(x)`

Arguments

`x` An atomic vector.

Value

A title-case character vector.

tolog	<i>Reshape columns into key/value rows</i>
-------	--

Description

Reshape columns into key/value rows

Usage

```
tolog(  
  data,  
  cols,  
  names = "variable",  
  values = "value",  
  idcols = NULL,  
  na.rm = FALSE  
)
```

Arguments

data	A data.frame.
cols	Character vector of column names.
names	Name for the resulting key/value column, depending on the function.
values	Vector or list of replacement values.
idcols	Columns to keep as row identifiers.
na.rm	Drop missing values before computing the result.

Value

A long-format basetable.

towide	<i>Reshape rows into columns</i>
--------	----------------------------------

Description

Reshape rows into columns

Usage

```
towide(data, names, values, idcols = NULL, fun = NULL, fill = NA)
```

Arguments

data	A data.frame.
names	Name for the resulting key/value column, depending on the function.
values	Vector or list of replacement values.
idcols	Columns to keep as row identifiers.
fun	Function applied to each element, column, or group.
fill	Value used for positions where no window/result is available.

Value

A wide-format basetable.

transliterate	<i>Transliterate text to ASCII</i>
---------------	------------------------------------

Description

Like `removeaccents()`, but also romanises the Greek and Cyrillic blocks (the Greek and Cyrillic spellings of "Athena" and "Moskva" fold to those ASCII forms), following ICU's Any-Latin; Latin-ASCII mapping. Other non-Latin scripts (Han, Kana, Arabic, Hebrew, Devanagari, Thai, ...) are left unchanged rather than guessed at. No Unicode library dependency.

Usage

```
transliterate(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A character vector the same length as x.

See Also

`removeaccents()` for Latin only.

Examples

```
# "Zurich", Greek "Athena", Cyrillic "Moskva" (spelt via code points so
# this help page stays ASCII)
greek <- intToUtf8(c(0x391, 0x3b8, 0x3ae, 0x3bd, 0x3b1))
cyrillic <- intToUtf8(c(0x41c, 0x43e, 0x441, 0x43a, 0x432, 0x430))
transliterate(c("Zurich", greek, cyrillic))
```

transpose	<i>Transpose a table</i>
-----------	--------------------------

Description

Transpose a table

Usage

```
transpose(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A transposed basetable.

traverse	<i>Traverse a list of arguments</i>
----------	-------------------------------------

Description

Call `.f` once per position across several equal-length vectors or lists, passing the *i*-th element of each as a positional argument. The parallel-map companion to [map\(\)](#).

Usage

```
traverse(.l, .f, ...)
```

Arguments

.l	A list of vectors or lists with a common length.
.f	A function or function name.
...	Additional arguments passed to <code>.f</code> .

Value

`traverse()` returns a list.

Examples

```
traverse(list(a = 1:2, b = 10:11), function(a, b) a + b)
```

<code>trim</code>	<i>Trim leading and trailing whitespace</i>
-------------------	---

Description

Trim leading and trailing whitespace

Usage

```
trim(x)
```

Arguments

`x` An atomic vector.

Value

A trimmed character vector.

<code>truncate</code>	<i>Truncate text with an ellipsis</i>
-----------------------	---------------------------------------

Description

Truncate text with an ellipsis

Usage

```
truncate(x, n, ellipsis = "...")
```

Arguments

`x` An atomic vector.
`n` Integer count.
`ellipsis` String appended to truncated text.

Value

A character vector.

types	<i>Column types</i>
-------	---------------------

Description

Return the column name, class, and storage type for each variable in a table.

Usage

types(data)

Arguments

data A data frame or data table.

Value

A data frame with one row per column.

unionrows	<i>Set union of rows</i>
-----------	--------------------------

Description

Set union of rows

Usage

unionrows(x, y, by = NULL)

Arguments

x An atomic vector.
y An atomic vector, data.frame, or basetable, depending on the function.
by Character vector of column names identifying groups or join keys.

Value

The union of x and y.

uniquerows	<i>Unique rows, in memory or straight off a delimited file</i>
------------	--

Description

Return unique rows, optionally considering only selected columns. With a single file path as data, it is a fused one-pass scan that returns the distinct combinations of cols without ever materialising the file as R vectors (see [aggregate\(\)](#)'s file mode).

Usage

```
uniquerows(data, cols = NULL, .keep_all = FALSE, ...)
```

Arguments

data	A data.frame, or a single path to a delimited text file.
cols	Optional character vector of columns used to determine uniqueness. Required when data is a file path.
.keep_all	Keep all columns when cols is supplied.
...	For the file form, passed to the file reader (where, delim, n_threads, ...).

Value

A basetable of the unique rows.

uniques	<i>Count of distinct values per column</i>
---------	--

Description

Count of distinct values per column

Usage

```
uniques(data)
```

Arguments

data	A data.frame.
------	---------------

Value

A named integer vector of distinct-value counts.

unite	<i>Combine several columns into one</i>
-------	---

Description

Combine several columns into one

Usage

```
unite(data, column, cols, sep = "_", remove = TRUE, na.rm = FALSE)
```

Arguments

data	A data.frame.
column	Name of a single column.
cols	Character vector of column names.
sep	Separator string.
remove	Drop the source column(s) after the operation.
na.rm	Drop missing values before computing the result.

Value

data with cols combined into column.

unmatchedkeys	<i>Distinct keys of x absent from y</i>
---------------	---

Description

Distinct keys of x absent from y

Usage

```
unmatchedkeys(x, y, by)
```

Arguments

x	An atomic vector.
y	An atomic vector, data.frame, or basetable, depending on the function.
by	Character vector of column names identifying groups or join keys.

Value

Rows of x whose key is not present in y.

unstack	<i>Unstack a table</i>
---------	------------------------

Description

Reshape a stacked table back into wide form.

Usage

```
unstack(data, form, ...)
```

Arguments

- data A data frame or data table.
- form A formula or equivalent description of the reshape.
- ... Additional arguments passed to the underlying method.

Value

A basetable reshaped into wide format.

updatemerge	<i>Update rows from another table</i>
-------------	---------------------------------------

Description

Update matching rows in x from y.

Usage

```
updatemerge(x, y, by, cols = NULL)
```

Arguments

- x, y Data frames or data tables.
- by Character vector of key columns.
- cols Optional columns to update.

Value

A basetable with selected columns updated from y.

upper	<i>Convert to upper case</i>
-------	------------------------------

Description

Convert to upper case

Usage

upper(x)

Arguments

x An atomic vector.

Value

An upper-case character vector.

week	<i>Extract the week of year</i>
------	---------------------------------

Description

Extract the week of year

Usage

week(x)

Arguments

x An atomic vector.

Value

An integer vector.

weekday	<i>Extract the weekday name</i>
---------	---------------------------------

Description

Extract the weekday name

Usage

```
weekday(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

A character vector.

winsorize	<i>Winsorize a vector at given quantiles</i>
-----------	--

Description

Winsorize a vector at given quantiles

Usage

```
winsorize(x, probs = c(0.01, 0.99))
```

Arguments

x	An atomic vector.
probs	Quantile probabilities.

Value

A winsorized numeric vector.

within	<i>Modify a table within an environment</i>
--------	---

Description

Evaluate expressions inside a table and return the modified result.

Usage

```
within(data, expr)
```

Arguments

data	A data frame or data table.
expr	An expression evaluated in the data's environment.

Value

A basetable containing the modified table.

year	<i>Extract the year</i>
------	-------------------------

Description

Extract the year

Usage

```
year(x)
```

Arguments

x	An atomic vector.
---	-------------------

Value

An integer vector.

yearday	<i>Extract the day of year</i>
---------	--------------------------------

Description

Extract the day of year

Usage

yearday(x)

Arguments

x An atomic vector.

Value

An integer vector.

Index

adddays, 7
addedrows, 8
addmonths, 8
addweeks, 9
addyears, 9
aggregate, 10, 117
aggregate(), 126
antimerge, 10
applyby, 11
applycols, 12
assert_cols, 17
assert_cols(), 12
assert_key(assert_cols), 17
assert_key(), 13
assertcols, 12
assertcomplete, 13
assertkey, 13
assertnames, 14
assertrange, 14
assertrows, 15
asserttype, 15
assertunique, 16
assertvalues, 16

base::lapply(), 63
base::Reduce(), 49
basetable (basetable-package), 7
basetable-package, 7
between dates, 17
blanktona, 18
btread, 18
btwrite, 20

cardinality, 21
casewhen, 22
ceilingdate, 22
center, 23
changedcols, 23
changedrows, 24
classes, 24

cleannames, 25
collapselevels, 25
collapsetext, 26
collapsevalues, 26
collapsevalues(), 22
colnames, 27
common_names(assert_cols), 17
common_names(), 27
commonnames, 27
compare, 28
compareschema, 28
compareschema(), 23
completegrid, 29
constants, 29
containstext, 30
convertcols, 30
count, 31, 117
countmatch, 31
crossmerge, 32
cumavg, 32
cumcount, 33
cumedist, 33

datediff, 34
dateseq, 34
day, 35
denserank, 35
describe, 36
difference, 36
diffrows, 37
dims, 37
drop, 38, 117
duplicated_keys(assert_cols), 17
duplicated_keys(), 38
duplicatekeys, 38
duplicatenames, 39
duplicaterows, 39

emptycols, 40
emptyrows, 40

endswith, [41](#)
equaldata, [41](#)
equalrows, [42](#)
expandlevels, [42](#)
expandrows, [43](#)
extract, [43](#)
extractall, [44](#)
extractbetween, [44](#)
extractint, [45](#)
extractnum, [45](#)

fillboth, [46](#)
filldown, [46](#)
fillup, [47](#)
firstby, [47](#)
firstcols, [48](#)
firstrows, [48](#)
floordate, [49](#)
foldr, [49](#)
freq, [50](#)

gregexpr(), [61](#)

headtail, [50](#)
hour, [51](#)

intersectrows, [51](#)
invalidrows, [52](#)
invalidvalues, [52](#)
isalpha, [53](#)
isalphanumeric, [53](#)
isblank, [54](#)
isemail, [54](#)
isintegertext, [55](#)
isnumerictext, [55](#)
isurl, [56](#)

joinrelationship, [56](#)
jointext, [57](#)

keepmissing, [57](#)

lagvalue, [58](#)
lastby, [58](#)
lastcols, [59](#)
lastrows, [59](#)
leadvalue, [60](#)
left, [60](#)
locate, [61](#)
locateall, [61](#)

lower, [62](#)
lump, [62](#)

map, [63](#)
map(), [123](#)
matchedkeys, [63](#)
matchestext, [64](#)
merge, [64](#), [71](#), [117](#)
middle, [65](#)
minute, [65](#)
missingindicator, [66](#)
missingness, [66](#)
missingrows, [67](#)
month, [67](#)
move, [68](#), [117](#)

naif, [68](#)
nato, [69](#)
natoblank, [69](#)
ncols, [70](#)
nearestmerge, [70](#)
nearesttext, [71](#)
nearesttext(), [113](#)
nonequimerge, [71](#)
normalizeencoding, [72](#)
normalizeunicode, [72](#)
nrows, [73](#)

omitmissing, [73](#)
orderrows, [74](#), [117](#)
outofrange, [74](#)
overlapmerge, [75](#)

padcenter, [75](#)
padleft, [76](#)
padright, [76](#)
parsecurrency, [77](#)
parsedate, [77](#)
parsedatetime, [78](#)
parsefailures, [78](#)
parseint, [79](#)
parselogical, [79](#)
parsenum, [80](#)
parsepercent, [80](#)
percentchange, [81](#)
percentrank, [81](#)
pick, [82](#), [117](#)
preview, [82](#)
profile, [83](#)

- propcount, 83
- quantilegroup, 84
- quarter, 84
- rangemerge, 85
- rbindfill, 85
- recode, 86
- regexpr(), 61
- removeaccents, 87
- removeaccents(), 122
- removeall, 87
- removedrows, 88
- removeduplicates, 88
- removetext, 89
- renamecols, 89, 117
- renamewith, 90
- reorderlevels, 90
- repairnames, 91
- replaceall, 91
- replacecols, 92
- replacetext, 92
- replacevalues, 93
- replacevalues(), 86, 91
- replacewhere, 93
- rescale, 94
- reshape (subset), 117
- reverse, 94
- right, 95
- rollapply, 95
- rollingmerge, 96
- rollingmerge(), 70
- rollmax, 97
- rollmean, 97
- rollmedian, 98
- rollmin, 99
- rollprod, 100
- rollsd, 100
- rollsum, 101
- rollvar, 102
- rounddate, 103
- rowall, 103
- rowany, 104
- rowapply, 104
- rowcount, 105
- rowfirst, 105
- rowlast, 106
- rowmax, 106
- rowmin, 107
- rownames, 107
- rownumber, 108
- sameschema, 108
- samplefrac, 109
- samplerows, 109
- second, 110
- semimerge, 110
- sentencecase, 111
- separate, 111
- setthreads, 112
- similartext, 112
- split, 113, 117
- splitfirst, 113
- splitlast, 114
- splitttext, 114
- squish, 115
- stack, 115, 117
- standardize, 116
- startswith, 116
- subset, 117
- summaries, 117, 118
- summarytab, 118
- textdist, 119
- textlen, 120
- titlecase, 120
- tolong, 121
- towide, 121
- transform (subset), 117
- transliterate, 122
- transliterate(), 87
- transpose, 123
- traverse, 123
- trim, 124
- truncate, 124
- types, 125
- unionrows, 125
- uniquerows, 117, 126
- uniques, 126
- unite, 127
- unmatchedkeys, 127
- unstack, 117, 128
- updatemerge, 128
- upper, 129
- utils::adist(), 119
- week, 129

weekday, [130](#)
winsorize, [130](#)
within, [117](#), [131](#)

year, [131](#)
yearday, [132](#)