

Package ‘lsmeans’

March 24, 2025

Type Package

Title Least-Squares Means

Version 2.30-2

Date 2025-03-24

Depends emmeans (≥ 1.3), methods, R (≥ 3.2)

ByteCompile yes

Description Obtain least-squares means for linear, generalized linear, and mixed models. Compute contrasts or linear functions of least-squares means, and comparisons of slopes. Plots and compact letter displays. Least-squares means were proposed in Harvey, W (1960) ``Least-squares analysis of data with unequal subclass numbers'', Tech Report ARS-20-8, USDA National Agricultural Library, and discussed further in Searle, Speed, and Milliken (1980) ``Population marginal means in the linear model: An alternative to least squares means'', The American Statistician 34(4), 216-221 <[doi:10.1080/00031305.1980.10483031](https://doi.org/10.1080/00031305.1980.10483031)>. NOTE: lsmeans now relies primarily on code in the 'emmeans' package. 'lsmeans' will be archived in the near future.

License GPL-2 | GPL-3

NeedsCompilation no

Author Russell Lenth [aut, cre, cph]

Maintainer Russell Lenth <russell-lenth@uiowa.edu>

Repository CRAN

Date/Publication 2025-03-24 17:40:02 UTC

Contents

lsmeans-package	2
ref.grid	2
ref.grid-class	3
transition	3

Index	5
--------------	----------

lsmeans-package	<i>Least-squares means</i>
-----------------	----------------------------

Description

This package provides methods for obtaining so-called least-squares means for factor combinations in a variety of fitted linear models. It can also compute contrasts or linear combinations of these least-squares means, (several standard contrast families are provided), and in addition can estimate and contrast slopes of trend lines. Popular adjustments for multiple-comparisons are provided, as well as graphical ways of displaying the results.

Almost the entire codebase for **lsmeans** now resides in the **emmeans** package (named for the more general term, “estimated marginal means”). **lsmeans** exists only as a transitional entity for the few remaining packages that depend on it.

Author(s)

Russell V. Lenth (author), Maxime Hervé (contributor)

Maintainer: Russ Lenth <russell-lenth@uiowa.edu>

References

Russell V. Lenth (2016) Least-Squares Means: The R Package lsmeans. *Journal of Statistical Software*, 69(1), 1-33. doi:10.18637/jss.v069.i01

Searle S.R. Speed F.M. Milliken G.A. (1980) Population marginal means in the linear model: An alternative to least squares means. *The American Statistician* **34**(4), 216-221.

ref.grid	<i>Create a reference grid from a fitted model</i>
----------	--

Description

These functions are provided in **lsmeans** because they have been renamed in **emmeans**

Usage

```
ref.grid(object, ...)
```

```
recover.data(object, ...)
```

```
lsm.basis(object, ...)
```

Arguments

object A model object in a supported class.

... Additional arguments passed to companion functions in the **emmeans** package.

Value

lsmeans now passes all its computations to **emmeans**, and the return values are thus what is returned by the corresponding functions [ref_grid](#), [recover_data](#), and [emm_basis](#), respectively.

Author(s)

Russell V. Lenth

Examples

```
fiber.lm <- lm(strength ~ machine + diameter, data = fiber)
rg <- ref.grid(fiber.lm, at = list(diameter = c(20, 24, 28)))
rg

# Note this is an emmGrid object defined in emmeans. The old "ref.grid"
# class is now an extension of this:
r.g. <- new("ref.grid", rg)
lsmeans(r.g., "machine")
```

ref.grid-class

The ref.grid and lsmobj classes

Description

The codebase for **lsmeans** is now mostly in **emmeans**. These two classes are simple extensions of the `emmGrid` class defined in **emmeans**, and are provided as support for objects created in older versions of **lsmeans**. For details, see [emmGrid-class](#).

Author(s)

Russell V. Lenth

transition

*Transition to **emmeans***

Description

The **lsmeans** package is being deprecated and further development will take place in its successor, **emmeans**. Users may use **emmeans** in almost exactly the same way as **lsmeans**, but a few function names and internal details are changed.

Details

In transitioning to **emmeans**, users will find that the vignettes are constructed quite differently and that, in those and in the documentation, emphasis is placed on “estimated marginal means” rather than “least-squares means”. The term “estimated marginal means” is broader and more appropriate for use with some models, e.g. ordinal regression, that don’t really involve least-squares methods. That is the reason for the change.

Accordingly, **emmeans** users are encouraged to use the functions `emmeans()`, `emtrends()`, `emmip()`, etc. in lieu of `lsmeans()`, etc. The latter functions *are still available* in **emmeans**; they run the corresponding `emmxxxx` function and relabel the results.

The **emmeans** package provides some functions that help convert scripts and R Markdown files containing **lsmeans** code so they will work in **emmeans**. There is also a function to convert `ref.grid` and `lsmobj` objects to the `emmGrid` objects used in **emmeans**. More extensive information is given in `vignette("transition-from-lsmeans", package = "emmeans")`.

Author(s)

Russell V. Lenth

Index

- * **htest**
 - lsmeans-package, 2
- * **models**
 - lsmeans-package, 2
 - ref.grid, 2
- * **package**
 - lsmeans-package, 2
- * **regression**
 - lsmeans-package, 2
 - ref.grid, 2

contrast (ref.grid), 2

emm_basis, 3

emmeans-transition (transition), 3

lsm.basis (ref.grid), 2

lsmeans (ref.grid), 2

lsmeans-package, 2

lsmobj-class (ref.grid-class), 3

recover.data (ref.grid), 2

recover_data, 3

ref.grid, 2

ref.grid-class, 3

ref_grid, 3

summary.ref.grid (ref.grid), 2

transition, 3