

# Package ‘modelDown’

October 13, 2022

**Title** Make Static HTML Website for Predictive Models

**Version** 1.1

**Description** Website generator with HTML summaries for predictive models.

This package uses 'DALEX' explainers to describe global model behavior.

We can see how well models behave (tabs: Model Performance, Auditor),

how much each variable contributes to predictions (tabs: Variable Response)

and which variables are the most important for a given model (tabs: Variable Importance).

We can also compare Concept Drift for pairs of models (tabs: Drifter).

Additionally, data available on the website can be easily recreated in current R session.

Work on this package was financially supported by the NCN Opus grant 2017/27/B/ST6/01307 at Warsaw University of Technology, Faculty of Mathematics and Information Science.

**Depends** R (>= 3.4.0)

**License** Apache License 2.0

**Encoding** UTF-8

**LazyData** true

**Imports** DALEX (>= 1.0), auditor (>= 0.3.0), ggplot2 (>= 3.1.0),  
whisker (>= 0.3-2), DT (>= 0.4), kableExtra (>= 0.9.0), psych  
(>= 1.8.4), archivist (>= 2.1.0), svglite (>= 1.2.1), devtools  
(>= 2.0.1), breakDown (>= 0.1.6), drifter (>= 0.2.1)

**Suggests** ranger, testthat, useful

**RoxygenNote** 7.1.0

**URL** <https://github.com/ModelOriented/modelDown>

**BugReports** <https://github.com/ModelOriented/modelDown/issues>

**NeedsCompilation** no

**Author** Przemysław Biecek [aut],  
Magda Tatarynowicz [aut],  
Kamil Romaszko [aut, cre],  
Mateusz Urbański [aut]

**Maintainer** Kamil Romaszko <kamil.romaszko@gmail.com>

**Repository** CRAN

**Date/Publication** 2020-04-15 00:30:03 UTC

## R topics documented:

modelDown . . . . . 2

**Index** . . . . . 4

modelDown *Generates a website with HTML summaries for predictive models*

### Description

Generates a website with HTML summaries for predictive models

### Usage

```
modelDown(..., modules = c("auditor", "drifter", "model_performance",
  "variable_importance", "variable_response"), output_folder = "output",
  repository_name = "repository", should_open_website = interactive())
```

### Arguments

... one or more explainers created with DALEX::explain() function. Pair of explainer could be provided to check drift of models

modules modules that should be included in the website

output\_folder folder where the website will be saved

repository\_name name of local archivist repository that will be created

should\_open\_website should generated website be automatically opened in default browser

### Details

Additional arguments that could be passed by name:

- remote\_repository\_path Path to remote repository that stores folder with archivist repository. If not provided, links to local repository will be shown.
- device Device to use. Tested for "png" and "svg", but values from ggplot2::ggsave function should be working fine. Defaults to "png".
- vr.vars variables which will be examined in Variable Response module. Defaults to all variables. Example vr.vars = c("var1", "var2")
- vr.type types of examinations which will be conducted in Variable Response module. Defaults to "pdp". Example vr.type = c("ale", "pdp")

### Author(s)

Przemysław Biecek, Magda Tatarynowicz, Kamil Romaszko, Mateusz Urbański

**Examples**

```

require("ranger")
require("breakDown")
require("DALEX")

# Generate simple modelDown page
HR_data_selected <- HR_data[1000:3000,]
HR_glm_model <- glm(left~., HR_data_selected, family = "binomial")
explainer_glm <- explain(HR_glm_model, data=HR_data_selected, y = HR_data_selected$left)

modelDown::modelDown(explainer_glm,
                      modules = c("model_performance", "variable_importance",
                                   "variable_response"),
                      output_folder = tempdir(),
                      repository_name = "HR",
                      device = "png",
                      vr.vars= c("average_monthly_hours"),
                      vr.type = "ale")

# More complex example with all modules
HR_ranger_model <- ranger(as.factor(left) ~ .,
                          data = HR_data, num.trees = 500, classification = TRUE, probability = TRUE)
explainer_ranger <- explain(HR_ranger_model,
                            data = HR_data, y = HR_data$left, function(model, data) {
  return(predict(model, data)$prediction[,2])
}, na.rm=TRUE)

# Two glm models used for drift detection
HR_data1 <- HR_data[1:4000,]
HR_data2 <- HR_data[4000:nrow(HR_data),]
HR_glm_model1 <- glm(left~., HR_data1, family = "binomial")
HR_glm_model2 <- glm(left~., HR_data2, family = "binomial")
explainer_glm1 <- explain(HR_glm_model1, data=HR_data1, y = HR_data1$left)
explainer_glm2 <- explain(HR_glm_model2, data=HR_data2, y = HR_data2$left)

modelDown::modelDown(list(explainer_glm1, explainer_glm2),
                      modules = c("auditor", "drifter", "model_performance", "variable_importance",
                                   "variable_response"),
                      output_folder = tempdir(),
                      repository_name = "HR",
                      remote_repository_path = "some_user/remote_repo_name",
                      device = "png",
                      vr.vars= c("average_monthly_hours", "time_spend_company"),
                      vr.type = "ale")

```

# Index

modelDown, [2](#)